



# **Methodologies for Calculating Baseline and Compliance Urban Per Capita Water Use**

*(For the Consistent Implementation of the  
Water Conservation Act of 2009)*

October 1, 2010

California Department of Water Resources  
Division of Statewide Integrated Water Management  
Water Use and Efficiency Branch

# Methodologies for Calculating Baseline and Compliance Urban Per Capita Water Use

October 1, 2010

**California Department of Water Resources**  
**Division of Statewide Integrated Water Management**  
**Water Use and Efficiency Branch**

State of California  
Arnold Schwarzenegger, Governor

The Natural Resources Agency  
Lester Snow, Secretary

Department of Water Resources  
Mark Cowin, Director

Sue Sims, Chief Deputy Director

Gerald Johns, Deputy Director      Dale Hoffman-Floerke, Deputy Director

Ralph Torres, Deputy Director      John Pacheco, Deputy Director

James Libonati, Deputy Director

Cathy Crothers, Acting Chief Counsel

Matt Notley, Assistant Director, Public Affairs Office

This Report was prepared under the direction of  
Division of Statewide Integrated Water Management  
Kamyar Guivetchi, Chief

By

Water Use and Efficiency Branch  
Manucher Alemi, Chief

Baryohay Davidoff, Land and Water Use Program Manager

Peter Brostrom, Urban Water Conservation Program Manager

Gwen Huff, Associate Land and Water Scientist

Tom Hawkins, Land and Water Use Program Manager (Retired Annuitant)

Toni Pezzetti, Engineering Geologist

Spencer Kenner, Staff Counsel

Richard Mills, Water Resources Control Engineer,  
State Water Resources Control Board (On Loan to DWR)

In consultation with

California Urban Water Conservation Council

Chris Brown, Executive Director

Elizabeth Betancourt, Program Manager

## Acknowledgement:

Technical Methodologies for Calculating Urban Water Use Targets was written with the assistance of the following consultants:

Stephen Hatchett, Senior Economist, CH2M HILL  
 Brian Van Lienden, Water Resources Engineer, CH2M HILL  
 Anil Bamezai, Principal, Western Policy Research  
 David Mitchell, Economist, M.Cubed

The Urban Stakeholder Committee provided significant guidance in developing this document. The Department of Water Resources would like to thank the members for their help

Ernesto Avila California Urban Water Agencies	William Granger Otay Water District	Loren Oki University of California, Davis
Tim Barr Western Municipal Water District	Richard Harris East Bay Municipal Utility District	Edwin Osann Natural Resources Defense Council
Joe Berg Municipal Water District of Orange County	Jack Hawks California Water Association	Toby Roy San Diego County Water Authority
Tim Blair Metropolitan Water District	Bob Kelly Suburban Water Systems	Fiona Sanchez Irvine Ranch Water District
David Bolland Association of California Water Agencies	Dave Koller Coachella Valley Water District	Bob Wilkinson University of California, Santa Barbara
Lisa Brown City of Roseville	Nora Laikam City of Fresno	John Woodling Sacramento Regional Water Authority
Heather Cooley Pacific Institute	Matthew Lyons Long Beach Water Department	
Mary Lou Cotton Kennedy/Jenks Consultants	Paul Selsky Brown and Caldwell	
Jerry De La Piedra Santa Clara Valley Water District	Henry McLaughlin City of Fresno	
Edwin de Leon Golden State Water Company	Jim Metropulos Sierra Club	
Chris Dundon Contra Costa Water District	John Mills Offices of John S. Mills	
Penny Falcon Los Angeles Dept of Water & Power	Lisa Morgan-Perales Inland Empire Utilities Agency	
Sharon Fraser El Dorado Irrigation District	Daniel Muelrath City of Santa Rosa	
Luis Generoso City of San Diego	Ron Munds City of San Luis Obispo	
	Tom Noonan Ewing Irrigation	

# Contents

---

<b>Introduction.....</b>	<b>8</b>
<b>Overview of Methodologies, Water Use Targets, and Reporting .....</b>	<b>10</b>
Methodologies .....	10
Baseline Water Use.....	11
Water Use Targets .....	11
Data Reporting.....	12
Consequences if Water Supplier Does Not Meet Water Use Targets .....	13
<b>Methodology 1: Gross Water Use .....</b>	<b>14</b>
Definition of Gross Water Use.....	14
Calculation of Gross Water Use .....	14
Step 1: Define the 12-month Calculation Period .....	14
Step 2: Delineate Distribution System Boundary.....	15
Step 3: Compile Water Volume from Own Sources .....	15
Step 4: Compile Imported Water Volume.....	16
Step 5: Compile Exported Water Volume .....	16
Step 6: Calculate Net Change in Distribution System Storage.....	18
Step 7: Calculate Gross Water Use before Indirect Recycled Water Use Deductions .....	18
Step 8: Deduct Recycled Water Used for Indirect Potable Reuse from Gross Water Use .....	18
Step 9: Calculate Gross Water Use after Deducting Indirect Recycled Water Use.....	20
Step 10 (Optional): Deduct from Gross Water Use the Volume of Water Delivered for Agricultural Use.....	21
Step 11 (Optional): Deduct Volume of Water Delivered for Process Water Use.....	21
Step 12: Calculate Gross Water Use after Optional Deductions .....	21
<b>Methodology 2: Service Area Population .....</b>	<b>24</b>
Definition of the Service Area Population .....	24
Estimating the Service Area Population.....	25
Category 1 Water Suppliers .....	26
Category 2 Water Suppliers .....	26
Category 3 Water Suppliers .....	26
Determining Adequacy of Current Population Estimate Methodology.....	26
Adjusting Population Estimates .....	27
<b>Methodology 3: Base Daily Per Capita Water Use .....</b>	<b>30</b>
Definition of Base Daily Per Capita Water Use.....	30
Calculation of Base Daily Per Capita Water Use .....	30
Calculating Base Daily Per Capita Water Use per Section 10608.20 .....	31

Distribution Area Expansion Caused by Mergers.....	31
Distribution Area Contraction.....	32
Distribution Area Expansion by Annexation of Already Developed Areas .....	32
Determining the Minimum Water Use Reduction Requirement per Section 10608.22 .....	32
Revisions to Base Daily Per Capita Water Use or Targets.....	35
<b>Methodology 4: Compliance Daily Per Capita Water Use.....</b>	<b>36</b>
Definition of Compliance Daily Per Capita Use .....	36
Estimation of Compliance-Year GPCD .....	36
Distribution Area Expansion Caused by Mergers.....	36
Distribution Area Contraction.....	36
Distribution Area Expansion by Annexation of Already Developed Areas .....	37
Distribution Area Expansion by Annexation of Undeveloped Areas .....	37
Existing Large Partial Customers Become Whole Customers .....	37
Water Supplier Subject to Urban Water Management Plan Reporting Requirements between 2010 and 2020.....	38
<b>Methodology 5: Indoor Residential Use .....</b>	<b>39</b>
Definition of Indoor Residential Use .....	39
<b>Methodology 6: Landscaped Area Water Use .....</b>	<b>40</b>
Definition of Landscaped Area Water Use .....	40
Approach to Calculating Landscaped Area Water Use .....	40
Identify Applicable MWELO for Each Parcel .....	41
Measure Landscaped Area.....	41
Measurement Techniques .....	42
Estimate Reference Evapotranspiration .....	43
Apply MAWA Equation to Calculate Annual Volume .....	44
Convert Annual Volume to GPCD .....	44
Summary of Steps to Calculate Landscaped Area Water Use .....	44
<b>Methodology 7: Baseline Commercial, Industrial, and Institutional Water Use .....</b>	<b>46</b>
Definition of Baseline CII Water Use.....	46
Use of Baseline CII Water Use .....	46
Calculation of Baseline CII Water Use.....	46
Process Water Exclusion.....	47
Adjustments for Multifamily Residential Connections .....	47
Adjustments for Residential Uses in CII Connections .....	48
<b>Methodology 8: Criteria for Adjustments to Compliance Daily Per Capita Water Use .....</b>	<b>49</b>
Definition of Adjustments to Compliance Daily Per Capita Water Use.....	49
Calculation of Adjustments to Compliance GPCD .....	49
<b>Methodology 9: Regional Compliance .....</b>	<b>50</b>
Legislative Guidance for Regional Compliance.....	50
Criteria for Water Suppliers that May Report and Comply as a Region.....	50
Tiered Regional Alliances.....	51
Calculation of Targets and Compliance GPCD.....	53
Calculation of Regional Targets .....	53

Calculation of Regional Compliance Daily Per Capita Water Use.....	53
Data Reporting for a Regional Alliance.....	54
Individual Supplier Urban Water Management Plans .....	54
Regional Urban Water Management Plans .....	54
Regional Alliance Report.....	55
Memoranda of Understanding or Agreements for Regional Alliances.....	55
Compliance Assessment for Water Suppliers Belonging to	
a Regional Alliance.....	55
Withdrawal from a Regional Alliance before 2020.....	56
Dissolution of a Regional Alliance before 2020.....	56
<b>APPENDIX A.....</b>	<b>57</b>
<b>Alternative Methodology for Service Area Population .....</b>	<b>57</b>
Step 1: Finalize Census Blocks in the 2000 Distribution Area .....	57
Step 2: Scale Population Information from Census Blocks to	
Distribution Area.....	58
Step 3: Obtain Population by Structure Type.....	59
Step 4: Obtain Active Connections Data .....	60
Step 5: Develop Population Estimates for Non-Census Years .....	61
Step 6: Further Improvements to Estimates.....	62
<b>APPENDIX B.....</b>	<b>63</b>
<b>Model Water Efficient Landscape Ordinance Definitions and Calculations .....</b>	<b>63</b>
<b>Appendix C.....</b>	<b>65</b>
<b>Method 4 for Determining Water Use Targets.....</b>	<b>65</b>
<b>Appendix D .....</b>	<b>66</b>
<b>Regulations for Implementing Process Water Provisions .....</b>	<b>66</b>

## Figures

Figure 1: Urban Retail Water Supplier System Schematic .....	17
Figure 2: Defining Area for Population Calculation .....	25
Figure 3: Suggested Process for Determining Adequacy of Service Area Population	
Estimate Methodology.....	29
Figure 4: 10 to 15 Year Base Daily Per Capita Water Use Calculations .....	31
Figure 5: Determination of Maximum Allowable 2020 GPCD Target .....	33
Figure 6: Example of Tiered Alliances.....	52
Figure A-1: Population per Residential Connection Method .....	61

## Tables

Table 1: Example Urban Retail Water Supplier Gross Water Use Calculation .....	22
Table 2: Example Calculation of Annual Deductable Volume of Indirect	
Recycled Water Entering Distribution System.....	23
Table 4: Base Daily Per Capita Water Use Calculation for Section 10608.22.....	34
Table 5: Base Daily Per Capita Water Use Calculation for Section 10608.20.....	34

# Introduction

---

In February 2008, Governor Arnold Schwarzenegger introduced a seven-part comprehensive plan for improving the Sacramento-San Joaquin Delta. A key component of his plan was a goal to achieve a 20 percent reduction in per capita water use statewide by the year 2020. The governor's inclusion of water conservation in the Delta plan emphasizes the importance of water conservation in reducing demand on the Delta and in reducing demand on the overall California water supply. In response to Schwarzenegger's call for statewide per capita savings, the Department of Water Resources (DWR) and the State Water Resources Control Board convened the 20x2020 Agency Team on Water Conservation. DWR released a draft 20x2020 Water Conservation Plan in April 2009 and the final 20x2020 Water Conservation Plan in February 2010. The water conservation plan developed estimates of statewide and regional baseline per capita water use and outlined recommendations to the governor on how a statewide per capita water use reduction plan could be implemented.

In November 2009, SBx7-7, The Water Conservation Act of 2009, was signed into law as part of a comprehensive water legislation package. The Water Conservation Act addresses both urban and agricultural water conservation. The urban provisions reflect the approach taken in the 20x2020 Water Conservation Plan. The legislation sets a goal of achieving a 20 percent statewide reduction in urban per capita water use and directs urban retail water suppliers to set 2020 urban water use targets.

The Water Conservation Act of 2009 directs DWR to develop technical methodologies and criteria to ensure the consistent implementation of the Act and to provide guidance to urban retail water suppliers in developing baseline and compliance water use. These technical methodologies were developed through a public process with stakeholder input. DWR has held two public listening sessions, five public stakeholder meetings, and two public workshops to receive comment on the technical methodologies. One of the methodologies, the Criteria for Compliance -Year Adjustment will be released in 2011. This methodology is not needed by urban water suppliers to develop 2010 urban water management plans, and additional time is needed to develop the weather normalization model, which will be a major component of the methodology.

Background documents, stakeholder meeting summaries and public comments related to the development of these methodologies are available at the Water Conservation Act of 2009 website: <http://www.water.ca.gov/wateruseefficiency/sb7/>



Or contact:

SBx7-7 Urban Water Conservation Program Manager

Water Use and Efficiency Branch

Department of Water Resources, 1416 Ninth Street, Sacramento CA 95814

# Overview of Methodologies, Water Use Targets, and Reporting

---

The Water Conservation Act of 2009 was incorporated into Division 6 of the California Water Code, commencing with Section 10608 of Part 2.55. All quotations of the Water Code in this report are from sections added by this legislation, unless otherwise noted.

The methodologies, water use targets, and reporting apply to urban retail water suppliers that meet a threshold of number of end users or annual volume of potable water supplied. Section 10698.12 (p) defines the water suppliers affected:

*“Urban retail water supplier” means a water supplier, either publicly or privately owned, that directly provides potable municipal water to more than 3,000 end users or that supplies more than 3,000 acre-feet of potable water annually at retail for municipal purposes.*

This overview summarizes the process that urban retail water suppliers must follow and the options they have for complying with the legislation.

## Methodologies

The legislation specifically calls for developing seven methodologies and a set of criteria for adjusting daily per capita water use at the time compliance is required (the 2015 and 2020 compliance years) under Section 10608.20(h):

- (1) *The department, through a public process and in consultation with the California Urban Water Conservation Council, shall develop technical methodologies and criteria for the consistent implementation of this part, including, but not limited to, both of the following:*
  - (A) *Methodologies for calculating base daily per capita water use, baseline commercial, industrial, and institutional water use, compliance daily per capita water use, gross water use, service area population, indoor residential water use, and landscaped area water use.*
  - (B) *Criteria for adjustments pursuant to subdivisions (d) and (e) of Section 10608.24.*

Sections 10608.20 and 10608.28 of the Water Code allow water suppliers the choice of complying individually or regionally by mutual agreement with other water suppliers or regional agencies. DWR has also developed a methodology for regional compliance.

The following methodologies are included in this report:

- Methodology 1: Gross Water Use
- Methodology 2: Service Area Population
- Methodology 3: Base Daily Per Capita Water Use

- Methodology 4: Compliance Daily Per Capita Water Use
- Methodology 5: Indoor Residential Use
- Methodology 6: Landscaped Area Water Use
- Methodology 7: Baseline Commercial, Industrial, and Institutional Water Use
- Methodology 8: Criteria for Adjustments to Compliance Daily Per Capita Water Use
- Methodology 9: Regional Compliance

The methodologies provide specific guidance to water suppliers on how to calculate baseline, target, and compliance-year water use. Each methodology defines how its calculations are to be used, with direct reference to the applicable section of the Water Code. Each methodology describes the calculations, data needed, and, where applicable, optional steps and alternative approaches that water suppliers may use depending on their specific circumstances.

The methodologies for indoor residential water use; landscaped area water use; and baseline commercial, industrial, and institutional water use (Methodologies 5, 6, and 7) apply only to urban retail water suppliers who use Method 2 (see Water Use Targets below) to set water use targets.

## Baseline Water Use

Water suppliers must define a 10- or 15-year base (or baseline) period for water use that will be used to develop their target levels of per capita water use. Water suppliers must also calculate water use for a 5-year baseline period, and use that value to determine a minimum required reduction in water use by 2026. The longer baseline period applies to a water supplier that meets at least 10 percent of its 2008 measured retail water demand through recycled water. Methodology 3: Base Daily Per Capita Water Use describes the calculations.

## Water Use Targets

An urban retail water supplier, as defined above, must set a 2020 water use target and a 2015 interim target using one of four methods. Three of these are defined in Section 10608.20(a)(1), with the fourth developed by DWR by the end of 2010. The 2020 water use target will be calculated using one of the following four methods:

- Method 1: Eighty percent of the water supplier's baseline per capita water use
- Method 2: Per capita daily water use estimated using the sum of performance standards applied to indoor residential use; landscaped area water use, and commercial, industrial, and institutional uses
- Method 3: Ninety-five percent of the applicable state hydrologic region target as stated in the State's April 30, 2009, draft 20x2020 Water Conservation Plan
- Method 4: An approach developed by DWR and reported to the Legislature by December 2010 (a description of this target method will be included as Appendix C)

The target may need to be adjusted further to achieve a minimum reduction in water use regardless of the target method (this is explained in Methodology 3). The Water Code directs that water suppliers must compare their actual water use in 2020 with their

calculated targets to assess compliance. In addition, water suppliers will report interim compliance in 2015 as compared to an interim target (generally halfway between the baseline water use and the 2020 target level). The years 2015 and 2020 are referred to in the methodologies as compliance years. All baseline, target, and compliance-year water use estimates must be calculated and reported in gallons per capita per day (GPCD).

Water suppliers have some flexibility in setting and revising water use targets:

- A water supplier may set its water use target and comply individually, or as part of a regional alliance (see Methodology 9: Regional Compliance).
- A water supplier may revise its water use target in its 2015 or 2020 urban water management plan or in an amended plan.
- A water supplier may change the method it uses to set its water use target and report it in a 2010 amended plan or in its 2015 urban water management plan. Urban water suppliers are not permitted to change target methods after they have submitted their 2015 UWMP.

## Data Reporting

DWR will collect data pertaining to urban water use targets through three documents: (1) through the individual supplier urban water management plans; (2) through the regional urban water management plans; and (3) through regional alliance reports.

Water suppliers that comply individually must report the following data in their urban water management plans (applicable urban water management plan dates are included in parentheses).

- Baseline Gross Water Use and Service Area Population (2010, 2015, 2020)
- Individual 2020 Urban Water Use Target (2010, 2015, 2020) and Interim 2015 Urban Water Use Target (2010)
- Compliance Year Gross Water Use (2015 and 2020) and Service Area Population (2010, 2015, 2020)
- Adjustments to Gross Water Use in the compliance year (2015, 2020)
- Water suppliers who choose Target Method 2 also must provide Landscaped Area Water Use and Baseline CII Water Use data (2010, 2015, 2020)
- Water Suppliers who choose Target Method 4 must provide the components of calculation as required by Target Method 4. Appendix C describes Target Method 4 and the regional compliance reporting that applies to that method (2010, 2015, 2020)

Water suppliers that comply regionally must fulfill additional reporting requirements. These are described in greater detail in Methodology 9: Regional Compliance.

## Consequences if Water Supplier Does Not Meet Water Use Targets

Each urban retail water supplier, as defined above, must comply by establishing 2015 and 2020 water use targets, demonstrating that its water use is in compliance with its targets, and reporting water use baselines, targets, compliance year water use, and supporting data in its urban water management plan. Section 10608.56 (a) states that a water supplier not in compliance will not be eligible for water grants or loans that may be administered by DWR or other state agencies:

*On and after July 1, 2016, an urban retail water supplier is not eligible for a water grant or loan awarded or administered by the state unless the supplier complies with this part.*

Two exceptions to this are allowed. Section 10608.56 (c) states that a water supplier shall be eligible for a water loan or grant if it “has submitted to the department for approval a schedule, financing plan, and budget, to be included in the grant or loan agreement, for achieving the per capita reductions.”

Section 10608.56 (e) states that a water supplier can also be eligible for a water loan or grant if it “has submitted to the department for approval documentation demonstrating that its entire service area qualifies as a disadvantaged community.”

# Methodology 1: Gross Water Use

---

## Definition of Gross Water Use

Section 10608.12(g) of the Water Code defines “Gross Water Use” as:

*the total volume of water, whether treated or untreated, entering the distribution system of an urban retail water supplier, excluding all of the following:*

- (1) Recycled water that is delivered within the service area of an urban retail water supplier or its urban wholesale water supplier*
- (2) The net volume of water that the urban retail water supplier places into long-term storage*
- (3) The volume of water the urban retail water supplier conveys for use by another urban water supplier*
- (4) The volume of water delivered for agricultural use, except as otherwise provided in subdivision (f) of Section 10608.24*

## Calculation of Gross Water Use

Gross Water Use is a measure of water supplied to the distribution system over 12 months and adjusted for changes in distribution system storage and deliveries to other water suppliers that pass through the distribution system. Recycled water deliveries are to be excluded from the calculation of Gross Water Use. Water delivered through the distribution system for agricultural use may be deducted from the calculation of Gross Water Use. Under certain conditions, industrial process water use also may be deducted from Gross Water Use.

The methodology for calculating Gross Water Use broadly follows American Water Works Association (AWWA) Manual M36 guidance for calculating Distribution System Input Volume.<sup>1</sup> Calculating Gross Water Use entails 12 basic steps, two of which are optional.<sup>2</sup>

### Step 1: Define the 12-month Calculation Period

Gross Water Use shall be calculated over a continuous 12-month period. This period can be based on the calendar year or the utility’s fiscal year.<sup>3</sup> The same 12-month period must be used in calculations of Gross Water Use for determining Base Daily Per Capita Water Use and Compliance Daily Per Capita Water Use.

---

<sup>1</sup> American Water Works Association, Manual of Water Supply Practices – M36: Water Audits and Loss Control Programs, 3rd Edition, 2009. M36 defines *Distribution System Input Volume* as the volume of water entering the distribution system to provide service to customers. It is equal to the water volume derived from the water utility’s own source waters, plus water imported or purchased, plus or minus the net change in water storage (if applicable and significant).

<sup>2</sup> AWWA Manual M36 contains several forms and worksheets that retail urban water suppliers can use to compile and organize data required to calculate Gross Water Use.

<sup>3</sup> As stipulated in paragraph (1) of subdivision (a) of Section 10608.20 of SBx7-7.

## Step 2: Delineate Distribution System Boundary

Water supply systems can be broadly subdivided between the transmission systems that convey large amounts of water to local storage reservoirs or treatment plants, and the distribution systems that supply water to residential, commercial, industrial, and public uses such as fire safety. Water distribution systems generally comprise large networks of pipes with complex branched and loop topologies with multiple flow paths to many delivery points.<sup>4</sup> In some systems, some retail customers receive water for municipal and industrial (M&I) uses directly from transmission canals and pipes, in which case the retail water supplier may treat the sections of the transmission canals and pipes delivering water to the retail M&I customers as part of its distribution system. However, transmission canals and pipelines not used for delivering water directly to retail customers should not be included as part of the distribution system.

Wherever possible, distribution system boundary limits should be defined by points of metering or measurement<sup>5</sup> of the water supply. Typical measurement locations for distribution include exit points for treatment plants, treated water reservoirs, wells feeding directly into the distribution system, and imported water entering directly into the distribution system. A schematic of a typical urban retail water supply system is shown in Figure 1; actual distribution systems may vary greatly in configuration. Therefore, each urban retail water supplier must define and delineate its distribution system for purposes of calculating Gross Water Use. The rules for defining and delineating the distribution system boundary must be applied consistently in the base period and compliance years.<sup>6</sup>

## Step 3: Compile Water Volume from Own Sources

The water supplier's own sources of supply entering the distribution system shall be identified and tallied. For systems that provide only treated water, this may consist mostly or entirely of water entering the distribution system from treatment plants (as in Figure 1). It may also include water from wells or other sources controlled by the water supplier that directly supply the distribution system (as in Figure 1).

Recycled water, as defined in subdivision (m) of Section 10608.12, *directly* entering the distribution system shall be excluded from the tally of own sources. Step 8 addresses how to account for recycled water *indirectly* entering the distribution system through potable reuse.

Measurement records for each source shall be compiled into annual volumes. AWWA's M36 manual or other appropriate references should be consulted in situations where water sources are unmetered or the water meters have not been routinely calibrated. Volumes for each source shall be reviewed and corrected for known errors that may exist in the raw

---

<sup>4</sup> <http://censam.mit.edu/news/posters/whittle/1.pdf>

<sup>5</sup> Measurements of unmetered agricultural and raw water deliveries must, at a minimum, meet an accuracy standard of +/- 6% by volume, as defined in the U.S. Bureau of Reclamation, Mid-Pacific Region's "2008 Conservation and Efficiency Criteria". Metered deliveries of M&I water must meet the measurement accuracy and calibration standards described in American Water Works Association Manual M6.

<sup>6</sup> For guidance on situations in which the distribution system boundary changed during the base period, see Methodology 3: Base Daily Per Capita Water Use. For situations in which the distribution system boundary changed during the compliance period, see Methodology 4: Compliance Daily Per Capita Water Use.

measurement data. Uncorrected metered volumes shall be adjusted based on the registration accuracy of the meter, as follows:<sup>7</sup>

$$\text{metered volume corrected} = \frac{\text{uncorrected metered volume}}{\text{registration accuracy expressed as a decimal}}$$

#### Step 4: Compile Imported Water Volume

Outside sources of finished water imported directly into the distribution system shall be identified and tabulated, excluding the following:

- Recycled water, as defined in subdivision (m) of Section 10608.12, imported from another water supplier
- Imported raw water passing through the urban retail water supplier's treatment plants, if that water has already been counted under Step 3 (as in Figure 1)

The raw measurement data shall be corrected for known errors in the same manner as for own source water.<sup>8</sup>

#### Step 5: Compile Exported Water Volume

Any water volumes sent through the distribution system to another water utility or jurisdiction shall be identified and tabulated. Recycled water, as defined in subdivision (m) of Section 10608.12, exiting the distribution system shall be excluded from the tabulation.<sup>9</sup> Bulk water exports that do not pass through the distribution system also shall not be counted. The raw metering data shall be corrected for known errors in the same manner as for own source and imported water.

<sup>7</sup> AWWA Manual M36 should be consulted if additional guidance on correcting raw meter data for meter registration inaccuracy is needed. Meters with errors exceeding AWWA standards should be recalibrated, repaired, or replaced.

<sup>8</sup> Generally, bulk water sale meters are routinely monitored for accuracy because they provide the basis for payment between the wholesaler and retailer.

<sup>9</sup> It is necessary to subtract recycled water exiting the system only if it was included in the tabulations of water entering the distribution system performed in Steps 3 and 4. However, the easiest way to handle recycled water directly entering the distribution system in the calculation of Gross Water Use is to exclude it entirely from each calculation step.






FIGURE 1  
URBAN RETAIL WATER SUPPLIER SYSTEM SCHEMATIC<sup>10</sup>

<sup>10</sup>Figure 1 provides a general depiction of all of the elements that may affect the calculation of Gross Water Use. Not all of these elements may be present in a particular water system, nor is it expected that Figure 1 will accurately characterize a particular system configuration.

## Step 6: Calculate Net Change in Distribution System Storage

If distribution system storage is greater at the end of the year than at the beginning, it indicates that water has entered the distribution system but has not been delivered to customers. This water would have been counted in Steps 3 and 4, but because it has not been delivered to customers, it must be deducted from the calculation of Gross Water Use. Conversely, a decrease in end-of-year distribution system storage indicates that water has been drawn from storage to meet customer demands. This water would not have been counted in Steps 1 and 2, and therefore must be added to the calculation of Gross Water Use. Note that these calculations apply only to storage in the distribution system. Do not include changes in storage outside the distribution system. If the change in distribution system storage is expected to be insignificant, or if data needed to calculate the change in distribution system storage are not available, the water supplier may forgo this step.

## Step 7: Calculate Gross Water Use before Indirect Recycled Water Use Deductions

Gross Water Use before Indirect Recycled Water Use Deductions equals the volume of water from own sources entering the distribution system determined in Step 3, plus the volume of water from imported water sources entering the distribution system determined in Step 4, less the volume of water delivered via the distribution system to other utilities determined in Step 5, less the net change in distribution system storage determined in Step 6.<sup>11</sup> Table 1 provides an example calculation.

## Step 8: Deduct Recycled Water Used for Indirect Potable Reuse from Gross Water Use

This step is necessary only if the urban retail water supplier uses recycled water (as defined in Subdivision (m) of Section 10608.12) to supplement raw surface or groundwater for indirect potable reuse. The Step 8 deduction requires the urban retail water supplier to estimate the amount of recycled water indirectly entering the distribution system through a surface or groundwater source (as in Figure 1).<sup>12</sup> This calculation requires three steps: (1) estimate the amount of recycled water used to supplement a surface reservoir source of supply, (2) estimate the amount of recycled water in extracted groundwater sources of supply, and (3) adjust these volumes for losses during transmission and treatment before the water enters the distribution system.

1. **Estimate recycled water used for surface reservoir augmentation.** The allowable deduction depends on the recycled water blend percentage in the surface reservoir water entering the potable water treatment plant. For example, if the raw surface water source is 95 percent fresh water and 5 percent recycled water, no more than 5 percent of the volume from this water source can be deducted from Gross Water Use calculated in Step 7. If the blend percentage of a surface water source is unknown, it shall be estimated based on the measured or estimated volumes of recycled water, local runoff, and imported water that entered the reservoir for the three years before the year for which Gross Water Use is being calculated. For example, if Gross Water Use is being calculated for 2005, the blend

---

<sup>11</sup> If the net change is negative, Gross Water Use will increase. If it is positive, Gross Water Use will decrease.

<sup>12</sup> Recycled water used for indirect potable use should only be subtracted at the time it enters the potable distribution system. It cannot be subtracted when placed into storage and again when extracted for potable use.

percentage is estimated by dividing the volume of recycled water that entered the reservoir by the total volume of water that entered the reservoir from 2002 through 2004.

2. **Estimate recycled water used for groundwater recharge.** Three approaches are allowed to estimate the amount of recycled water extracted from groundwater and introduced into a distribution system. Because year-to-year variations can occur in the amount of recycled water applied in a groundwater recharge operation, long-term running averages are required.
  - a. **Monitoring data at extraction wells.** If monitoring data are available to enable determination of the percent of extracted water at each extraction well that originated as recycled water (for example, using geochemical analysis), then such data can be used to estimate the amount of recycled water entering a distribution system. To account for year-to-year variations, the credit for recycled water is a five-year running monthly average percentage for each well for the preceding 60 months. For recharge projects in operation less than 60 months, a period of 60 months can be created using a combination of actual monitoring data since initiation of recharge operations and projected data. The projected data can be based on an acceptable groundwater model as described in paragraph b below or a projected average of extraction using the procedure described in paragraph c below.
  - b. **Groundwater model for extraction wells.** If a groundwater model is available that has the capability of tracking the movement of recycled water from recharge operations to extraction wells and estimating the percent of extracted groundwater that originated as recycled water at each well operated by the water supplier based on actual historic data of recycled water applied at groundwater recharge operations, then such data can be used to determine the amount of recycled water entering a distribution system. The groundwater model must be calibrated and approved as part of an adjudication or other regulatory process, such as the groundwater permitting process by the California Department of Public Health or a California Regional Water Quality Control Board. To account for year-to-year variations, the credit for recycled water is a five-year running monthly average percentage at each well for the preceding 60 months. For recharge projects in operation less than 60 months, the monthly running average may be derived from the model using all months of actual recycled water applied in a recharge operation and projected recycled water amounts planned to be applied for a future period to reach a combined total of 60 months of operation.
  - c. **Recharge data less in-basin losses.** Where actual extraction well monitoring data or estimated data obtained from an accepted groundwater model, as described in paragraph b above, are unavailable, an estimate can be made of extracted recycled water based on amounts of recycled water applied in recharge operations adjusted for an in-basin loss factor. The allowable deduction depends on the product of three factors:
    - The average annual volume of recycled water recharged into the groundwater basin for the purpose of indirect potable reuse over the 5 years before the year for which Gross Water Use is being calculated. For recharge projects in operation less than 60 months, data from all months of actual recharge operations may be

combined with projected volumes of recycled water recharge to reach a combined total of 60 months of operation to calculate the average annual volume of recycled water recharged.

- A loss factor to account for water losses during recharge and extraction. If a loss factor has been developed as part of a groundwater management plan, a basin adjudication process, or some similar regulatory process, the water supplier shall use that loss factor and provide reference to the appropriate documentation. If a loss factor has not been developed as part of a local regulatory process, the water supplier shall use a default loss factor of 10 percent.<sup>13</sup> The default loss factor of 10 percent is not applicable to groundwater recharge operations intended as seawater intrusion barriers. For seawater intrusion barriers, the loss factor will be determined on a case-by-case basis.
- The volume of water pumped from the basin by the urban retail water supplier expressed as a percentage of the total volume of water pumped by all water users extracting water from the basin in the year for which Gross Water Use is being calculated.

For example, if the average annual recharge of recycled water for the five years before the year for which Gross Water Use is being calculated is 500 acre-feet (AF), the recharge loss factor is 10 percent, and the urban retail water supplier accounted for 25 percent of the volume of water pumped from the basin in the year for which Gross Water Use is being calculated, then no more than 113AF  $= (500 \times (1.0 - 0.10) \times 0.25)$  from this supply source can be deducted from Gross Water Use calculated in Step 7.

3. **Adjust for losses.** Only deduct the volume of recycled water used for indirect potable reuse that enters the distribution system from Gross Water Use calculated in Step 7. Loss factors for transmission and treatment based on recent system audit data (or other reliable sources for estimating transmission and treatment losses) shall be applied to the estimated volumes of recycled water. For example, if the volume of recycled water before transmission and treatment is estimated to be 1,000 AF, and combined losses from transmission and treatment are estimated to be 3 percent, only 970 AF shall be deducted from Gross Water Use calculated in Step 7.

Table 2 shows an example calculation of the volume of recycled water used for indirect potable reuse based on approach 2.c above.

## Step 9: Calculate Gross Water Use after Deducting Indirect Recycled Water Use

This equals the volume of water determined in Step 7 less the volume of water determined in Step 8. Table 1 shows an example calculation of Gross Water Use after indirect recycled water use deductions.

<sup>13</sup> The default value of 10 percent is based on the loss factors applied to groundwater storage in the Arvin-Edison and Semitropic Water Storage Districts. It also is consistent with the range of 0 to 15 percent loss factors applied to California water storage projects identified in the Groundwater Banking Programs Survey-Results and Summary Report prepared for the Sacramento Groundwater Authority by Kennedy/Jenks Consultants (2008). The projects they surveyed primarily used modeling and observation to determine the specific loss factor for each project.

### Step 10 (Optional): Deduct from Gross Water Use the Volume of Water Delivered for Agricultural Use

This step is necessary only if the urban retail water supplier has chosen to exclude from the calculation of Gross Water Use water delivered for agriculture per Section 10608.12 (g) (4). Consideration of agricultural water use must be the same for calculations of Gross Water Use for determining Base Daily Per Capita Water Use and Compliance Daily Per Capita Water Use.

Identify and tabulate the volume of water delivered through the distribution system for agricultural water uses. Do not include deliveries that bypass the distribution system (see Figure 1 for examples of agricultural deliveries inside and outside the distribution system). Delivery volumes shall be based on account records and meter data for connections in the distribution system used to supply water for the commercial production of agricultural crops or livestock.<sup>14</sup>

### Step 11 (Optional): Deduct Volume of Water Delivered for Process Water Use

This step is necessary only if the urban retail water supplier has elected to exclude process water from the calculation of Gross Water Use *and* the supplier is eligible to do so. An urban retail water supplier is eligible to exclude process water from the calculation of Gross Water Use only if its industrial water use comprises a substantial percentage of total water use. [NOTE: See Appendix D for guidance on whether to include or exclude process water.]

### Step 12: Calculate Gross Water Use after Optional Deductions

This equals the volume of water determined in Step 9 less the volume of water determined in Steps 10 and 11. Table 1 provides an example calculation of Gross Water Use after optional deductions.

---

<sup>14</sup> The standard used to identify distribution system connections supplying agricultural water uses is based on subdivision (b) of Section 535 of the California Water Code. Commercial agricultural production is defined by the U.S. Department of Agriculture and the Census Bureau as any place from which \$1,000 or more of agricultural products (crops and livestock) were sold or normally would have been sold during the year. For the purposes of calculating Gross Water Use, retail nursery water use is not considered to be an agricultural water use.

TABLE 1  
EXAMPLE URBAN RETAIL WATER SUPPLIER GROSS WATER USE CALCULATION

Utility Name:	12-month period: 1-Jan to 31-Dec					Volume Units: Million Gallons				
Calculation	Year 1	Year 2	Year 3	Year 4	Year 5	Year 6	Year 7	Year 8	Year 9	Year 10
Volume from Own Sources (raw data)	3,480.8									
Meter error adjustment (+/-)	136.9									
<i>Subtotal: Corrected Volume from Own Sources</i>	3,617.7									
Volume from Imported Sources (raw data)	1,005.0									
Meter error adjustment (+/-)	39.5									
<i>Subtotal: Corrected Volume from Imported Sources</i>	1,044.5									
<b>Total Volume Into Dist. System = Line 1 + Line 2</b>	<b>4,662.2</b>									
Volume Exported to Other Utilities (raw data)	432.0									
Meter error adjustment (+/-)	17.3									
<i>Subtotal: Corrected Volume Exported to Other Utilities</i>	449.3									
Change in Dist. System Storage (+/-)	-8.6									
<b>Gross Water Use Before Indirect Recycled Water Use Deductions = Line 3 - Line 4 - Line 5</b>	<b>4,221.5</b>									
Indirect Recycled Water Use Deduction	304.3									
<b>Gross Water Use After Indirect Recycled Water Use Deductions = Line 6 - Line 7</b>	<b>3,917.2</b>									
<i>Water Delivered for Ag. Use (optional deduction)</i>	0.0									
<i>Process Water Use (optional deduction)</i>	278.8									
<b>Gross Water Use After Optional Deductions = Line 8 - Line 9 - Line 10</b>	<b>3,638.4</b>									

**TABLE 2**  
**EXAMPLE CALCULATION OF ANNUAL DEDUCTABLE VOLUME OF INDIRECT RECYCLED WATER ENTERING DISTRIBUTION SYSTEM**

Surface Reservoir Augmentation			Volume Discharged from Reservoir for Distribution System Delivery (MG)	Recycled Water Blend	Recycled Water Delivered to Treatment Plant (MG)	Transmission/Treatment Loss	Transmission/Treatment Losses (MG)	Volume Entering Distribution System (MG)
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)
					(4) x (5)		(6) x (7)	(6) – (8)
Source 1			1,000	5%	50	3%	1.5	48.5
Source 2			500	10%	50	3%	1.5	48.5
<i>Subtotal Reservoir Augmentation:</i>								<i>97.0</i>
Groundwater Recharge	5-Year Annual Average Recharge (MG)	Recharge Recovery Factor	Recycled Water Pumped from Basin (MG)	Utility Pumping as % of Basin Total	Recycled Water Pumped by Utility (MG)	Transmission/Treatment Loss	Transmission/Treatment Losses (MG)	Volume Entering Distribution System (MG)
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)
			(2) x (3)		(4) x (5)		(6) x (7)	(6) – (8)
Basin 1	500	90%	450	25%	113	3%	3.4	109.1
Basin 2	750	90%	675	15%	101	3%	3.0	98.2
<i>Subtotal Groundwater Recharge:</i>								<i>207.3</i>
<b>Deductable Volume of Indirect Recycled Water Entering Distribution System:</b>								<b>304.3</b>

Note:

MG = million gallons

# Methodology 2: Service Area Population

---

## Definition of the Service Area Population

Section 10608.20(f) states:

*When calculating per capita values for the purposes of this chapter, an urban retail water supplier shall determine population using federal, state, and local population reports and projections.*

The legislation directs DWR to develop consistent methodologies and criteria for determining Service Area Population.

To obtain an accurate estimate of GPCD, water suppliers must estimate population of the areas that they actually serve, which may or may not coincide with either their jurisdictional boundaries or with the boundaries of cities. Customers may be in the distribution area with a wholly private supply during the baseline and compliance years, and new areas may be annexed into a water supplier's distribution system over time. The area used for calculating Service Area Population shall be the same as the distribution system area used in Methodology 1, Gross Water Use.

Figure 2 illustrates the many different situations that may arise, with the background grid indicating the census blocks that overlap with the water supplier's service area boundary. Examples include the following:

- The actual distribution area may cover only a portion of the jurisdictional boundary.
- Large water users that depend wholly or partially on a private groundwater supply (e.g., college campus, a military installation, a correctional facility) may exist in the distribution area. If such a user is wholly dependent on private supply, its residents should be excluded. If the user is partially dependent (for example, it uses a municipal source for indoor use and private groundwater wells for irrigation only), its residents served by the municipal source should be included. Estimation of compliance GPCD for customers that switch their irrigation to a municipal source between the baseline and compliance years is addressed in Methodology 4: Compliance Daily Per Capita Water Use.
- New customers outside the present distribution area may connect to the water supplier's distribution system in the future for various reasons.
- The water supplier's distribution system can geographically expand over time as a result of economic and population growth.

Although a water supplier may consult any or all federal, State, and local data sources to estimate population, these estimates must account for the above-mentioned complexities.






FIGURE 2  
DEFINING AREA FOR POPULATION CALCULATION

## Estimating the Service Area Population

Data published by the California Department of Finance (DOF) or the U.S. Census Bureau must serve as the foundational building block for population estimates. In some instances, data published by these two sources may be directly applicable. In other instances, additional refinements may be necessary. For example, to account for distribution areas that do not match city boundaries, customers with private sources of supply, or other unique local circumstances, water suppliers may have to supplement the above sources of data with additional local data sources such as county assessor data, building permits data, and traffic analysis zone data. These refinements are acceptable as long as they are consistently applied over time, and as long as they build upon population data resources of the DOF or the U.S. Census Bureau. Suppliers in any category listed below may use the persons per-connection or person per housing unit population calculation method described in Appendix A.

Retail water suppliers will generally fall into one of the following three categories:

- Category 1: Water suppliers whose *actual distribution area* overlaps substantially ( $\geq 95\%$ ) with city boundaries (may be a single city or a group of cities) during baseline and compliance years
- Category 2: Water suppliers not falling in Category 1 but having an electronic geographic information system (GIS) map of their distribution area

- Category 3: Water suppliers not falling in Category 1 and lacking an electronic GIS map of their distribution area.

### Category 1 Water Suppliers

These water suppliers are encouraged to use population data published by the DOF's demography unit. However, population data may also be available through a water wholesaler, a local government agency, or an association of local governments. A list of associations of local governments is available through the California Association of Councils of Government (CALCOG: [www.calcog.org](http://www.calcog.org)). Many of these associations serve as census-data repositories and also have GIS capabilities.

Category 1 water suppliers may use population estimates from any of these federal, state, or local agencies, as long as they clearly cite their data source, use the same source for both the baseline and compliance years, and correct these estimates for privately supplied large customers that may exist in their actual distribution area (for development of these corrections, see Appendix A).

### Category 2 Water Suppliers

These water suppliers have two options:

- Water suppliers that are members of an association of local governments (or a water wholesaler) that develop population estimates for its members using GIS maps of actual distribution areas and population data from the DOF or Census Bureau should use these data for the baseline and compliance years. These suppliers are not required to use the per-connection or per-housing unit methodology described in Appendix A. The water suppliers should coordinate with the local government association or wholesaler to complete the task of identifying and removing large institutions with wholly private systems in their distribution area.
- Water suppliers without such membership must develop population estimates using either a per-connection or per-housing unit methodology described in Appendix A or another equivalent method that uses data either from the DOF or the U.S. Census Bureau as its basis.

### Category 3 Water Suppliers

These water suppliers have the same two options as Category 2 water suppliers. The only difference is that to access the U.S. Census Bureau's population data resources, they first must identify which census blocks fall in their distribution area. This exercise can be performed manually (see Appendix A), or the distribution area map boundary can be digitized. Category 3 water suppliers may be able to access these digitization capabilities and census-based population estimation capabilities through their local association of governments. Alternatively, they can develop population estimates using either the per-connection or per-housing unit methodology described in Appendix A or another equivalent method that uses data from either the DOF or the U.S. Census Bureau as its basis.

### Determining Adequacy of Current Population Estimate Methodology

Figure 3 provides a flow chart to help water suppliers determine whether their existing population estimation methodology is adequate or must be refined. If refinement is needed,

it should be coordinated with the water wholesaler or the local association of governments that currently provides population estimates. Water suppliers that currently lack access to reliable population estimates that reflect characteristics of their actual distribution areas can use the per-connection methodology described in Appendix A.

## Adjusting Population Estimates

Population increases in existing developed areas or high-density infill redevelopments are estimated annually by DOF for incorporated cities and unincorporated portions of counties. These and other sources of local data may be used to estimate population for the non-census years. For water suppliers using the methodology described in Appendix A, population changes largely will be captured through the persons-per-connection ratios applied to changes in counts of active connections over time.

Water suppliers may revise population estimates for baseline years between 2000 and 2010 when 2010 census information becomes available. DWR will examine discrepancy between the actual 2010 population estimate and the DOF's projections for 2010. If significant discrepancies are discovered, DWR may require some or all suppliers to update their baseline population estimates.

Service area boundaries may also contract or expand during the baseline period. The latter could occur because of annexation of previously developed areas that may have been dependent upon private groundwater wells in the past but have subsequently become part of an urban retail water supplier's system. The following list provides guidance under various annexation scenarios. Additional adjustments may be required to population estimates for events that occur between the baseline and compliance years. These issues are discussed in Methodology 4: Compliance Daily Per Capita Use.

- If a portion of the distribution area is removed during one of the baseline years, water suppliers must compute their baseline after eliminating this removed portion from all their baseline years.
- If an area was annexed before the first baseline year, or the annexation involves merger with another urban retail water supplier, no data issues arise. In the latter case, population and connections data would be available for each water supplier separately. If not, appropriate estimates should be developed and documented.
- If the area was annexed before 2000, population estimates should be developed for the annexed area using the census block and person-per-connection method outlined in Appendix A, or an equivalent method.
- If the area was annexed after 2000, the water supplier will know the connection count only in the year of the annexation, not in 2000 and corresponding to the population estimate. Water suppliers may apply person-per-connection ratios developed for their pre-annexation distribution area to estimate population in the annexed area, or use other defensible techniques. For example, they could obtain county assessor data to back-cast what connection counts would have been in the annexed area in 2000 to permit scaling of census population estimates for the annexed areas to the post-annexation years. These can be further improved after 2012 once data from the 2010 census become available.

Water suppliers in other unique situations, such as those experiencing a significant change in their seasonal workforce or seasonal resident population between the baseline and compliance years, may adjust their population estimates using other techniques. The water supplier must provide documentation that the technique is based on or consistent with DOF or U.S. Census Bureau population data.




FIGURE 3  
SUGGESTED PROCESS FOR DETERMINING ADEQUACY OF SERVICE AREA POPULATION ESTIMATE  
METHODOLOGY

# Methodology 3: Base Daily Per Capita Water Use

---

## Definition of Base Daily Per Capita Water Use

Base Daily Per Capita Water Use is defined as average gross water use, expressed in GPCD, for a continuous, multiyear base period. The Water Code specifies two different base periods for calculating Base Daily Per Capita Water Use under Section 10608.20 and Section 10608.22:

- The first base period is a 10- to 15-year continuous period, and is used to calculate baseline per capita water use per Section 10608.20.
- The second base period is a continuous five-year period, and is used to determine whether the 2020 per capita water use target meets the legislation's minimum water use reduction requirement per Section 10608.22.

Unless the urban retail water supplier's five-year Base Daily Per Capita Water Use per Section 10608.12 (b) (3) is 100 GPCD or less, Base Daily Per Capita Water Use must be calculated for both baseline periods.

## Calculation of Base Daily Per Capita Water Use

Calculating Base Daily Per Capita Water Use entails four steps:

1. Estimate Service Area Population for each year in the base period using Methodology 2.
2. Calculate Gross Water Use for each year in the base period using Methodology 1. Express Gross Water Use in gallons per day (gpd).<sup>15</sup>
3. Calculate daily per capita water use for each year in the base period. Divide Gross Water Use (determined in Step 2) by Service Area Population (determined in Step 1).
4. Calculate Base Daily Per Capita Water Use. Calculate average per capita water use by summing the values calculated in Step 3 and dividing by the number of years in the base period. The result is Base Daily Per Capita Water Use for the selected base period.

---

<sup>15</sup> If Gross Water Use is expressed in million gallons per year, multiply by 1,000,000 and then divide the result by 365. If Gross Water Use is expressed in acre-feet, multiply by 325,851 and then divide the result by 365.




FIGURE 4  
10 TO 15 YEAR BASE DAILY PER CAPITA WATER USE CALCULATIONS

## Calculating Base Daily Per Capita Water Use per Section 10608.20

Calculate Base Daily Per Capita Water Use using one of the following base periods:

- If recycled water made up less than 10 percent of 2008 retail water delivery, use a continuous 10-year period ending no earlier than December 31, 2004, and no later than December 31, 2010.
- If recycled water made up 10 percent or more of 2008 retail water delivery, use a continuous 10- to 15-year period ending no earlier than December 31, 2004, and no later than December 31, 2010.

Figure 4 illustrates the procedure. If Gross Water Use and/or population are not available for the full base period, the water supplier shall calculate base daily per capita water use for the maximum number of years for which data are available. When selecting between base periods, the water supplier shall select the base period for which the most data are available. For example, if gross water use and/or population data are not available before 1997, the water supplier shall select a base period starting in 1997.

### Distribution Area Expansion Caused by Mergers

If two or more water suppliers merged wholly, or one water supplier acquired a portion of another's service area, during a year that falls in the baseline period of the merged entity, they should derive their baseline GPCD as if they were a single entity for the entire baseline period to stay consistent with the targets and compliance GPCDs that would represent the merged entity.

## Distribution Area Contraction

If during the baseline period a previously served portion of the distribution system is removed from a water supplier's service area, the baseline GPCD shall be corrected to reflect only that portion of the service area that remained consistently supplied during the baseline and compliance years.

## Distribution Area Expansion by Annexation of Already Developed Areas<sup>16</sup>

For areas annexed during the baseline years, water suppliers can select one of two choices:

- Include these areas for baseline GPCD estimation and test compliance for the combined entity.
- Track baseline and compliance GPCDs for the annexed areas separately.

## Determining the Minimum Water Use Reduction Requirement per Section 10608.22

The following calculation is required only if the five-year baseline per capita water use per Section 10608.12 (b) (3) is greater than 100 gpcd. The calculation is used to determine whether the water supplier's 2015 and 2020 per capita water use targets meet the legislation's minimum water use reduction requirement per Section 10608.22. The calculation entails three steps:

1. Calculate Base Daily Per Capita Water Use using a continuous five-year period ending no earlier than December 31, 2007, and no later than December 31, 2010.<sup>17</sup>
2. Multiply the result from Step 1 by 0.95. The 2020 per capita water use target cannot exceed this value (unless the water supplier's five year baseline per capita water use is 100 gpcd or less). If the 2020 target is greater than this value, reduce the target to this value.
3. Set the 2015 target to the mid-point between the 10- or 15-year baseline per capita water use and the 2020 target determined in Step 2.

As an example, suppose a water supplier has a 10-year baseline per capita water use (per Section 10608.20) of 170 GPCD, and a 5-year baseline per capita water use (per Section 10608.22) of 168 GPCD.

- The maximum allowable GPCD target in 2020 (per Section 10608.22) is  $0.95 \times 168 \text{ GPCD} = 160 \text{ GPCD}$ .
- The 2020 target under Method 1 is  $0.8 \times 170 \text{ GPCD} = 136 \text{ GPCD}$ .

<sup>16</sup> Annexation here refers to already developed and inhabited areas that may have relied upon groundwater until this point in time, or on other sources of water for which data are not available, and that were not previously connected to a municipal source. This is not to be confused with annexation of previously undeveloped land. No adjustment is required for the latter type of annexation, whose impact on GPCD is naturally accounted for by the estimation of base period Gross Water Use and Service Area Population.

<sup>17</sup> If 5 years of continuous data are not available, use the maximum number of years for which data are available.



Because the Method 1 target is less than 160 GPCD, no further adjustment to the 2020 target is required if Method 1 is used.

Suppose the water supplier's 2020 target under Method 3 is 167 GPCD. Because this is greater than 160 GPCD, the target would need to be reduced to 160 GPCD if Method 3 is used.

Similarly, if a target calculated using Method 2 or 4 exceeded 160 GPCD, it would need to be reduced to 160 GPCD in order to satisfy the legislation's minimum water use reduction requirement. Figure 5 shows how the five-year baseline per capita water use amount is used to determine whether the 2020 target meets the legislation's minimum water use reduction requirement.




FIGURE 5  
DETERMINATION OF MAXIMUM ALLOWABLE 2020 GPCD TARGET

Tables 4 and 5 may be used to organize the information needed to calculate Base Daily Per Capita Water Use under Sections 10608.20 and 10608.22.

**TABLE 4**  
**BASE DAILY PER CAPITA WATER USE CALCULATION FOR SECTION 10608.22**

Utility Name: \_\_\_\_\_

12-month Period: \_\_\_\_\_ to \_\_\_\_\_

(1)	(2)	(3)	(4)
Base Years <sup>#</sup>	Service Area Population	Gross Water Use (gal. per day)	Daily Per Capita Water Use (3) ÷ (2)
Year 1			
Year 2			
Year 3			
Year 4			
Year 5			
Total of Column (4):			
Divide Total by 5:			

<sup>#</sup>Most recent year in base period must end no earlier than December 31, 2007, and no later than December 31, 2010.

**TABLE 5**  
**BASE DAILY PER CAPITA WATER USE CALCULATION FOR SECTION 10608.20**

Utility Name: \_\_\_\_\_

12-month Period: \_\_\_\_\_ to \_\_\_\_\_

(1)	(2)	(3)	(4)
Base Years*	Service Area Population	Gross Water Use (gal. per day)	Daily Per Capita Water Use (3) ÷ (2)
Year 1			
Year 2			
Year 3			
Year 4			
Year 5			
Year 6			
Year 7			
Year 8			
Year 9			
Year 10			
Year 11			
Year 12			
Year 13			
Year 14			
Year 15			
Total of Column (4):			
Divide Total by Number of Base Years:			

\* Enter the actual year of the data in this column. The most recent year in base period must end no earlier than December 31, 2004, and no later than December 31, 2010. The base period cannot exceed 10 years unless at least 10 percent of 2008 retail deliveries were met with recycled water.

## Revisions to Base Daily Per Capita Water Use or Targets

A water supplier may revise its calculated Base Daily Per Capita Water Use after submitting its 2010 urban water management plan if better information becomes available. The revisions may be included in the water supplier's 2015 and subsequent plans or may be submitted as an amended plan, provided it follows the process required for amendments to such plans. If the revisions to the Base Daily Per Capita Water Use changes the water use target, the water use target must be revised as well.

In addition, a water supplier may change the method it uses to set its water use target, and report the method change and target revision in a 2010 amended plan or in its 2015 urban water management plan. Target method changes are not permitted in the 2020 plan or amended 2015 plans.

# Methodology 4: Compliance Daily Per Capita Water Use

---

The following methodology addresses estimation of compliance daily per capita water use (in GPCD) in the years 2015 and 2020.

## Definition of Compliance Daily Per Capita Use

Section 10608.12(e) states:

*“Compliance daily per-capita use” means the gross water use during the final year of the reporting period, reported in gallons per capita per day.*

## Estimation of Compliance-Year GPCD

Methodology 1: Gross Water Use and Methodology 2: Service Area Population shall be used to develop the two basic components for estimating compliance-year GPCD. This section discusses adjustments to compliance-year GPCD because of changes in distribution area caused by mergers, annexation, and other scenarios that occur between the baseline and compliance years.

Adjustments are allowed in calculating compliance-year GPCD for factors described in Section 10608.24. These adjustments are discussed in Methodology 8: Criteria for Compliance-Year Adjustment.

### Distribution Area Expansion Caused by Mergers

If water suppliers merge, or one water supplier acquires a portion of another’s service area, between the baseline period and the compliance year, they have two choices:

- Test compliance separately for each service area.
- Calculate a (compliance year) population weighted average of each system’s target and determine compliance as a single entity using this weighted average.

### Distribution Area Contraction

If a previously supplied portion included in the baseline is removed from the distribution area before the compliance years, water suppliers shall re-compute their baseline GPCD after eliminating the removed portion for all baseline years.

## Distribution Area Expansion by Annexation of Already Developed Areas <sup>18</sup>

For areas annexed between the baseline and compliance years, a water supplier must determine Base Daily Per Capita Water Use, target water use, and compliance water use.

- Base Daily Per Capita Water Use for the annexed area shall be determined using the same baseline period as the water supplier's original service area (before the annexation). If such data are not available, the water supplier shall use a baseline period starting with the earliest year available for the annexed area and including ten years, if available. If no data exist for years before annexation, the water supplier shall use data from the year of annexation.
- Annexed areas shall be assigned a prorated target based upon the number of years between annexation and the end of 2020. For example, if a water supplier's target is based on a 20 percent reduction by 2020, and it annexes an area in 2017, this annexed area should show a 6 percent reduction in GPCD by 2020 relative to its 2017 GPCD.
- Compliance may be determined for the separate service areas (annexed and original), or for the combined service area using a (compliance year) population weighted average.

If compliance is determined separately for separate service areas, both areas must be in compliance for supplier to be in compliance.

## Distribution Area Expansion by Annexation of Undeveloped Areas

No special adjustment calculation is needed for areas that were undeveloped during the baseline period but which were annexed and developed between the baseline period and compliance year. The impact on GPCD is accounted for by the estimation of compliance-year Gross Water Use and compliance-year population.

## Existing Large Partial Customers Become Whole Customers

Large customers that pump groundwater or take surface water for landscape irrigation or other uses (depending on their municipal source solely for indoor use) may switch and use only the municipal source. This change will disrupt the baseline and compliance year comparison. Two adjustments are provided below:

- If the switch occurs during the baseline years, the landscape irrigation or other use should be included in the compliance-year gross water calculation.
- If the switch occurs between the baseline and compliance years, the water associated with irrigation use switches, properly documented and subjected to the requirements of the Model Water Efficient Landscape Ordinance adopted by DWR in 2009, may be excluded from the calculation of compliance-year Gross Water Use. Otherwise, the irrigation or other use must be included in both the baseline and compliance year gross water use calculations.

---

<sup>18</sup> Annexation here refers to already developed and inhabited areas that may have relied upon groundwater until this point in time and were not previously connected to a municipal source.

## **Water Supplier Subject to Urban Water Management Plan Reporting Requirements between 2010 and 2020**

Water suppliers that become subject to urban water management plan reporting requirements after 2010 also become subject to the new requirements of Section 10608 of the Water Code from the same year onward. These water suppliers are required to estimate their baseline GPCD and establish their 2020 GPCD targets using the same methodological guidelines that apply to other water suppliers. However, for testing compliance, such water suppliers may prorate these targets depending on the year the water supplier became subject to the new requirements.

For example, if a water supplier chooses a 2020 target that is 20 percent below its baseline GPCD, but it became subject to the new requirements only in 2017, it shall test compliance against a target that is 6 percent below its baseline GPCD.

# Methodology 5: Indoor Residential Use

---

## Definition of Indoor Residential Use

Section 10608.20(b)(2)(A) states:

*For indoor residential water use, 55 gallons per capita daily water use as a provisional standard. Upon completion of the department's 2016 report to the Legislature pursuant to Section 10608.42, this standard may be adjusted by the Legislature by statute.*

Section 10608.42 states:

*The department shall review the 2015 urban water management plans and report to the Legislature by December 31, 2016, on progress towards achieving a 20-percent reduction in urban water use by December 31, 2020. The report shall include recommendations on changes to water efficiency standards or urban water use targets in order to achieve the 20-percent reduction and to reflect updated efficiency information and technology changes.*

Section 10608.20(b)(2)(A) sets a provisional standard for efficient indoor use (55 GPCD) that urban retail water suppliers using target Method 2 must use to set their 2020 target. However, they are not required to demonstrate that this indoor residential target has actually been met—only that the overall target, which includes additional components for landscaped area water use and commercial, industrial, and institutional (CII) water use, has been met.

Section 10608.42 requires DWR to submit a report to the Legislature in 2016 that will include recommendations on changes to water use efficiency standards to reflect updated efficiency information and technological changes. DWR will conduct a study to assess whether the provisional indoor residential standard of 55 GPCD should be adjusted.

Based on the report DWR submits in 2016, the Legislature may change the indoor residential standard. The indoor residential standard is used only to set the target under Method 2; calculation of indoor usage by water supplier is not required for determining compliance with Method 2.

## Methodology 6: Landscaped Area Water Use

---

The calculation of Landscaped Area Water Use requires a measurement (or estimate) of landscaped area and of the landscape water use per unit area (based on reference evapotranspiration [ET]). As with other urban water use measures under Section 10608, Landscaped Area Water Use is defined as a daily per capita rate of water use; consequently, Methodology 2: Service Area Population is used in calculating Landscaped Area Water Use.

### Definition of Landscaped Area Water Use

For the Landscaped Area Water Use component of target Method 2, Section 10608.20 (b)(2)(B) states:

*For landscape irrigated through dedicated or residential meters or connections, water efficiency equivalent to the standards of the Model Water Efficient Landscape Ordinance set forth in Chapter 2.7 (commencing with Section 490) of Division 2 of Title 23 of the California Code of Regulations, as in effect the later of the year of the landscape's installation or 1992. An urban retail water supplier using the approach specified in this subparagraph shall use satellite imagery, site visits, or other best available technology to develop an accurate estimate of landscaped areas.*

All landscape irrigated by dedicated or residential meters must be included, including multifamily residential parcels. Definitions and calculations contained in the Model Water Efficient Landscape Ordinance (MWELo) are provided in Appendix B. These calculations give the Landscaped Area Water Use as a function of landscaped area and reference ET. The MWELo defines landscaped area as planting areas, turf areas, and water features. Landscaped area excludes footprints of buildings or structures, sidewalks, driveways, parking lots, decks, patios, gravel or stone walks, other pervious or non-pervious hardscapes, and other non-irrigated areas designated for non-development (such as open spaces and existing native vegetation). Section 10608.20 (b)(2)(B) restricts the landscaped area to include only landscape irrigated through dedicated or residential meters or connections.

Landscaped area for the purposes of calculating the Method 2 target shall mean the water supplier's estimate or measurement of 2020 landscaped areas. Water suppliers shall develop a preliminary estimate (forecast) of 2020 landscaped areas for purposes of setting urban water use targets and interim urban water use targets under Subdivision 10608.20 (a) (1). For final compliance-year calculations, water suppliers shall update the estimate of 2020 landscaped areas using one of the techniques described in the following sections.

### Approach to Calculating Landscaped Area Water Use

Water suppliers shall follow five steps to calculate Landscaped Area Water Use:

1. Identify applicable MWELo (1992 or 2010) for each parcel.
2. Estimate irrigated landscaped area for each parcel.



3. Determine reference evapotranspiration for each parcel.
4. Use the Maximum Applied Water Allowance (MAWA) equation from the applicable MWELo to calculate annual volume of landscaped area water use.
5. Convert annual volume to GPCD.

### Identify Applicable MWELo for Each Parcel

Before computing landscaped area, water suppliers must determine how MWELo ordinances apply to specific parcels in their service areas. Two versions of MWELo apply according to the date when landscaping was installed in a given parcel:

- For landscaped areas installed on or after January 1, 2010, the MAWA equation and all applicable criteria from the 2009 version of the ordinance or its equivalent shall be used.
- For landscaped areas installed before January 1, 2010, the MAWA equation and all applicable criteria from the 1992 version of the ordinance or its equivalent shall be used.

For the purposes of this methodology, two important differences between the two ordinances are the ET adjustment factor and the inclusion of a special landscaped area for calculating a water allowance in the 2010 ordinance. The applicable definitions and calculations in these ordinances are provided in Appendix B.

Landscaped Area Water Use shall be calculated for each parcel (or groups of parcels with the same reference ET and applicable MWELo) using Maximum Applied Water Allowance (MAWA) computations from the applicable MWELo.

Water suppliers should use the best available information to determine which MWELo applies to each parcel. This may include date of submittal for MWELo design review, date of service establishment, and remote sensing information.

The calculations provided in Appendix B will yield water use estimates in gallons per year. The total Landscaped Area Water Use for the water supplier will equal the total Landscaped Area Water Use of all parcels in the water supplier's service area. Because Landscaped Area Water Use is defined in units of GPCD, the result of the calculation above must be divided by Service Area Population and then converted from annual to daily use.

### Measure Landscaped Area

The water supplier shall select a technique for measuring landscaped area that satisfies the following criteria:

- The landscaped area must be measured or estimated for all parcels served by a residential or dedicated landscape water meter or connection in the water supplier's service area.
- Only irrigated landscaped area served by residential or dedicated landscape water meter or connection shall be included in the calculation of Landscaped Area Water Use. Landscape served by CII connections and non-irrigated landscape shall be excluded. (All references to landscaped area below shall mean irrigated landscaped area served by a residential or dedicated landscape meter or connection.)

## Measurement Techniques

The following sections describe techniques that may be used to measure landscaped area. Water suppliers may use one or a combination of these techniques.

**Field-Based Measurement.** Field-based measurement of parcels' landscaped area may be accomplished by physical measurement using devices such as a total station, measuring wheel and compass, global positioning system (GPS), or other measuring devices having accuracy similar to these devices. Field-based measurement also may be obtained from landscape designs submitted to the water supplier for compliance with the MWELo or for other planning and billing purposes.

**Measuring with Remote Sensing.** The landscaped area may be measured by using remote sensing (aerial or satellite imaging) to identify the landscaped areas in conjunction with a GIS representation of the parcels in the water supplier's service area. A variety of remote-sensing techniques are available, and additional techniques may become available between now and 2020. DWR will allow the water supplier to select the remote-sensing technique that it prefers. However, the following conditions shall be met:

- The remote-sensing information must be overlaid onto a GIS representation of each parcel boundaries to estimate the irrigated landscaped area in each parcel.
- The remote-sensing imagery must have a resolution of 1 meter or less per pixel.
- The remote-sensing technique must be verified for accuracy by comparing its results to the results of field-based measurement for a subset of parcels selected using random sampling. The water supplier shall report the resulting percent error between the estimates of landscaped area produced by the remote-sensing technique and those produced by field-based measurements for the sampled parcels.
- DWR has not set its own standards for remote-sensing verification and sampling design. The water supplier shall provide a description of its remote-sensing technique (including imagery, data processing, and verification) when it reports its landscaped area for purposes of complying with provisions of the Water Code. Congalton and Green (1999)<sup>19</sup> and Stein et al. (2002)<sup>20</sup> are two references that describe professional standards for remote sensing.

**Using Sampling to Estimate Landscaped Area on Small Parcels.** The landscaped area for smaller-sized parcels may be calculated by measuring the percentage of total parcel area that is landscaped in a sample of similar parcels and applying that percentage to the remaining parcels. This technique may be used only for parcels with a total land area of 24,000 square feet or less. The parcels for which this technique is used shall be divided into groups, or strata, based on parcel size increments of 4,000 square feet or less. (For example, parcels up to 4,000 square feet would form one group, parcels between 4,001 and 8,000 square feet would form another group, and so forth.) Field-based measurement or remote sensing must be used to calculate the landscaped area for a subset of parcels sampled at random in each parcel size group. The percentage of landscaped area to total

<sup>19</sup> Congalton, R. G., and K. Green, 1999. *Assessing the Accuracy of Remotely Sensed Data: Principles and Practices*. CRC Press, Boca Raton, FL.

<sup>20</sup> Stein, A., F. van der Meer, and B. Gorte, eds. 2002. *Spatial Statistics for Remote Sensing*. Kluwer Academic Publishers, Netherlands.

land area for the sampled parcels in each group can then be used to calculate the landscaped area for all other parcels in the group. Parcels greater than 24,000 square feet shall be measured directly.

Statistical sampling is a means to provide adequate information at reasonable cost. If implemented carefully, sampling allows the water supplier to develop accurate estimates of landscaped area for all relevant parcels from a subset of parcels. However, sampling shall not be used to estimate landscaped area for parcels larger than 24,000 square feet. Stratified sampling (random sampling in identified subgroups of parcels) should be used to estimate the landscaped area in different parcel size groups, as described earlier. Other characteristics of parcels may be used as a basis for selecting the strata in addition to parcel size.

DWR has not developed specific standards for sampling design. Urban water suppliers should follow standards of professional practice sufficient to demonstrate unbiased estimates of landscaped area. For example, Cochran (1977)<sup>21</sup> and Lohr (2010)<sup>22</sup> provide guidance for sound sampling design.

**Other Measurement Techniques.** The water supplier may use another technique to measure landscaped area for each parcel other than the ones described previously if one becomes available in the future. However, the technique must meet similar conditions to those described above for remote sensing:

- The landscaped area information must be gathered or reported on a parcel basis, or it must be overlaid onto a GIS representation of each parcel's boundaries to calculate the landscaped area in each parcel.
- The technique must be tested for accuracy by comparing its results to the results of field-based measurement for a subset of parcels. Field-based measurement should be performed for a subset of parcels selected at random from those for which the technique has been used. The water supplier should report the percent error between the calculations of landscaped area produced by the selected technique and those produced by field-based measurements for the sampled parcels.

## Estimate Reference Evapotranspiration

Calculations under the MWEL0 require determination of reference ET. Each parcels served by a residential or dedicated landscape water meter or connection in the water supplier's service area shall be assigned a reference ET based on one of the following methods:

- Appendix A of the 2009 ordinance contains tables of reference ET. In some cases, the water supplier may choose a single reference ET value most appropriate for all parcels in its service area. For parcels in geographic areas not covered in the Appendix A table, the ordinance provides the following direction for selecting the appropriate reference value: "For geographic areas not covered in Appendix A, use data from other cities located nearby in the same reference evapotranspiration zone, as found in the CIMIS Reference Evapotranspiration Zones Map, Department of Water Resources, 1999."

---

<sup>21</sup> Cochran, William G. 1977. *Sampling Techniques*. 3rd edition. Wiley; NY, NY.

<sup>22</sup> Lohr, Sharon. 2010. *Sampling: Design and Analysis*. Brooks/Cole Cengage, Boston, MA. 2nd edition.

- DWR has developed a spatial program (Spatial CIMIS) that provides interpolated ET data between weather stations.<sup>23</sup> The program can provide estimates of reference ET for any part of California with a resolution of 2 kilometer (km) by 2 km. Water suppliers may use this tool to assign reference ET to parcels. Any other CIMIS enhancements or additional stations formally adopted by DWR between 2010 and 2020 also may be used.
- Water suppliers may use local reference ET estimates that are not formally part of CIMIS or that make adjustments to CIMIS station estimates, provided that such estimates or adjustments are scientifically derived and of comparable reliability to CIMIS estimates. The water supplier shall explain why neither the CIMIS nor other approved DWR reference ET information is adequate, and shall provide the data and calculations used to develop the local reference ET estimate.

## Apply MAWA Equation to Calculate Annual Volume

Appendix B provides the MAWA equations that apply to parcels. These equations, or their equivalents, will yield water use estimates in gallons per year. The total Landscaped Area Water Use for the water supplier will equal the total Landscaped Area Water Use of all parcels in the supplier's service area.

## Convert Annual Volume to GPCD

After the MAWA for all parcels has been summed to determine the total Landscaped Area Water Use portion of the Method 2 target, the total must be divided by Service Area Population and then by 365 to calculate the Landscaped Area Water Use in GPCD. Refer to Methodology 2: Service Area Population to complete this step. Because Landscaped Area Water Use is defined in units of GPCD, the result must be converted from annual to daily use.

## Summary of Steps to Calculate Landscaped Area Water Use

Calculating Landscaped Area Water Use requires the following process:

1. Assign applicable MWELO (1992 or 2009) to each parcel.
2. Estimate landscaped area for each parcel.
  - d. Select measurement technique(s) for landscaped area (for example, field based, remote sensing, or sampling).
  - e. Apply technique(s) to calculate total landscaped area for each parcel. (This applies only to parcels for which landscaped area has not yet been measured.)
  - f. Measure special landscape area (SLA) where applicable.
3. Determine the reference ET for each parcel.
4. Use the MAWA from the applicable MWELO to calculate Landscaped Area Water Use for all parcels.

---

<sup>23</sup> California Irrigation Management Information System. The spatial model is available at <http://www.cimis.water.ca.gov/cimis/cimiSatSpatialCimis.jsp>.

- a. Use the equations, or their equivalents, to calculate the MAWA for each parcel or group of parcels (grouped according to applicable MWELO, reference ET, and presence of SLA).
  - b. Sum the MAWA over all parcels to calculate the total annual Landscaped Area Water Use portion of the Method 2 target.
5. Divide the total from Step 4 by Service Area Population and then by 365 to calculate the Landscaped Area Water Use in GPCD.

# Methodology 7: Baseline Commercial, Industrial, and Institutional Water Use

---

Baseline Commercial Industrial and Institutional (CII) Water Use is needed for urban water use target Method 2 (along with the indoor residential and landscape uses). It also affects the adjustment factors that agencies may consider at the time of testing compliance in 2015 and 2020 by allowing them to make adjustments based on “substantial changes” in CII relative to Baseline CII Water Use per Section 10608.24 (d)(1)(B). The definition of “substantial change” and adjustments are discussed in Methodology 8: Criteria for Adjustments to Compliance Daily Per Capita Water Use.

## Definition of Baseline CII Water Use

Section 10608.12 defines Baseline CII Water Use and related concepts as follows:

- (c) *“Baseline commercial, industrial, and institutional water use” means an urban retail water supplier’s base daily per capita water use for commercial, industrial, and institutional users.*
- (d) *“Commercial water user” means a water user that provides or distributes a product or service.*
- (h) *“Industrial water user” means a water user that is primarily a manufacturer or processor of materials as defined by the North American Industry Classification System code sectors 31 to 33, inclusive, or an entity that is a water user primarily engaged in research and development.*
- (i) *“Institutional water user” means a water user dedicated to public service. This type of user includes, among other users, higher education institutions, schools, courts, churches, hospitals, government facilities, and nonprofit research institutions.*

## Use of Baseline CII Water Use

Urban retail water suppliers are given several methods for calculating water use targets. Method 2 allows them to calculate a target by using three components: Indoor Residential Use, Landscaped Area Water Use, and Baseline CII Water Use. Section 10608.20 (b)(2)(C) specifies that the CII portion of the target is to be calculated as follows:

*For commercial, industrial, and institutional uses, a 10 percent reduction in water use from the baseline commercial, industrial, and institutional water use by 2020.*

## Calculation of Baseline CII Water Use

Baseline periods that a retail water supplier may use to determine Baseline CII Water Use shall follow the same direction required for Base Daily Per Capita Water Use under Section 10608.12.(b):

*“Base daily per capita water use” means any of the following:*

- (1) The urban retail water supplier’s estimate of its average gross water use, reported in gallons per capita per day and calculated over a continuous 10-year period ending no earlier than December 31, 2004, and no later than December 31, 2010.*
- (2) For an urban retail water supplier that meets at least 10 percent of its 2008 measured retail water demand through recycled water that is delivered within the service area of an urban retail water supplier or its urban wholesale water supplier, the urban retail water supplier may extend the calculation described in paragraph (1) up to an additional five years to a maximum of a continuous 15-year period ending no earlier than December 31, 2004, and no later than December 31, 2010.*

A retail water supplier must have CII data for the entire baseline period used in the water supplier’s calculation of Base Daily Per Capita Water Use. If the CII data do not exist, the retail water supplier should use another water use target method.

For each year in the baseline period, the volume of Baseline CII Water Use shall be divided by the Service Area Population (see Methodology 2), and the average of those calculations, converted to a daily rate, is the Baseline CII Water Use for the purpose of calculating the Method 2 target as defined in Section 10608.20(b)(2). The procedure for averaging the annual per capita CII use is the same as for calculating Base Daily Per Capita Water Use (refer to Methodology 3: Base Daily Per Capita Water Use).

The CII component of the 2020 target for Method 2 shall be the Baseline CII Water Use (in GPCD) multiplied by 0.9.

## Process Water Exclusion

A retail water supplier may elect to exclude process water from its calculation, consistent with Section 10608.24(e):

*When developing the urban water use target pursuant to Section 10608.20, an urban retail water supplier that has a substantial percentage of industrial water use in its service area, may exclude process water from the calculation of gross water use to avoid a disproportionate burden on another customer sector.*

If a water supplier elects to exclude process water, it must do so for baseline and compliance year per capita water use and for baseline CII water use. DWR regulations that define when and how process water can be excluded from Gross Water Use and Baseline CII Water Use calculations are provided in Appendix D.

## Adjustments for Multifamily Residential Connections

A retail water supplier whose baseline CII data includes some multifamily residential uses must demonstrate that it can accurately adjust the data to remove those uses.

In cases where the retail water supplier can estimate the population in multifamily residences included in the CII data, the supplier must do both of the following:

1. Use the adjustment procedure described below in Adjustments for Residential Uses in CII Connections to remove indoor residential uses from the CII data.
2. Assure that landscaped area in the CII data is excluded from the calculations of Landscaped Area Water Use.

In situations where the supplier cannot estimate the population in multifamily residences included in the CII data, Method 2 cannot be used to set the water supplier's water use target.

## Adjustments for Residential Uses in CII Connections

Some CII connections also may serve group quarters or other residential uses. Examples could include campus dormitories, military base housing, and apartments that are served by a CII connection. Water use target Method 2 already provides an indoor use allowance of 55 GPCD for such residents. To ensure that this indoor use is not double-counted, the following steps must be used to adjust the CII component of the target water use under Method 2:

1. Estimate the average population served by CII connections during the baseline period and whose residents use is included in the water supplier's unadjusted Baseline CII Water Use.
2. Calculate the average daily volume of target Indoor Residential Use associated with this population by multiplying the result of Step 1 by the 55-GPCD target indoor use specified for Method 2.
3. Convert the unadjusted CII GPCD target (the Baseline CII Water Use times 0.9) to an average daily volume by multiplying by Service Area Population.
4. Subtract the average daily volume calculated in Step 2 from the unadjusted CII daily volume calculated in Step 3.
5. Divide the result from Step 4 by Service Area Population to give the adjusted Baseline CII Water Use in GPCD for use in calculating the water use target for Method 2.



# Methodology 8: Criteria for Adjustments to Compliance Daily Per Capita Water Use

---

## Definition of Adjustments to Compliance Daily Per Capita Water Use

Section 10608.24(d) states:

- (1) *When determining compliance daily per capita water use, an urban retail water supplier may consider the following factors:*
  - (A) *Differences in evapotranspiration and rainfall in the baseline period compared to the compliance reporting period.*
  - (B) *Substantial changes to commercial or industrial water use resulting from increased business output and economic development that have occurred during the reporting period.*
  - (C) *Substantial changes to institutional water use resulting from fire suppression services or other extraordinary events, or from new or expanded operations, that have occurred during the reporting period.*
- (2) *If the urban retail water supplier elects to adjust its estimate of compliance daily per capita water use due to one or more of the factors described in paragraph (1), it shall provide the basis for, and data supporting, the adjustment in the report required by Section 10608.40.*

## Calculation of Adjustments to Compliance GPCD

To be developed.

[Application of these adjustments will not occur until a compliance year. This methodology requires further development including completion of weather normalization modeling. Expected completion date is early 2011. ]

## Methodology 9: Regional Compliance

---

According to Sections 10608.20(a)(1) and 10608.28, urban retail water suppliers may plan, comply, and report on a regional, an individual basis or both. Each group of water suppliers agreeing among themselves to plan, comply, and report as a region is referred to in this Methodology as a “regional alliance.”

### Legislative Guidance for Regional Compliance

Section 10608.20(a)(1) states:

*Each urban retail water supplier shall develop urban water use targets and an interim urban water use target by July 1, 2011. Urban retail water suppliers may elect to determine and report progress toward achieving these targets on an individual or regional basis, as provided in subdivision (a) of Section 10608.28, and may determine the targets on a fiscal year or calendar year basis.*

Section 10608.28 states:

- (a) An urban retail water supplier may meet its urban water use target within its retail service area, or through mutual agreement, by any of the following:*
  - (1) Through an urban wholesale water supplier.*
  - (2) Through a regional agency authorized to plan and implement water conservation, including, but not limited to, an agency established under the Bay Area Water Supply and Conservation Agency Act (Division 31 (commencing with Section 81300)).*
  - (3) Through a regional water management group as defined in Section 10537.*
  - (4) By an integrated regional water management funding area.*
  - (5) By hydrologic region.*
  - (6) Through other appropriate geographic scales for which computation methods have been developed by the department.*
- (b) A regional water management group, with the written consent of its member agencies, may undertake any or all planning, reporting, and implementation functions under this chapter for the member agencies that consent to those activities. Any data or reports shall provide information both for the regional water management group and separately for each consenting urban retail water supplier and urban wholesale water supplier.*

### Criteria for Water Suppliers that May Report and Comply as a Region

To form a regional alliance, water suppliers must meet at least one of the following criteria:

- Water suppliers are recipients of water from a common wholesale water supplier. For this purpose, the State Water Project and the Central Valley Project are not considered wholesale water suppliers. Wholesale water suppliers are not required to establish and meet targets for daily per capita water use. Wholesale water suppliers serving in the role of a regional alliance are representing the urban retail water suppliers that are members of the alliance and compliance with a regional target is on behalf of the member suppliers and not the wholesaler supplier itself.
- Water suppliers are partners with a common regional agency authorized to plan and implement water conservation.
- Water suppliers are part of a regional water management group as defined in Water Code section 10537.
- Water suppliers are part of an integrated regional water management funding area, which for this purpose is interpreted to mean an Integrated Regional Water Management (IRWM) planning area.
- Water suppliers are located in the same hydrologic region, which for this purpose refers to the 10 hydrologic regions as shown in the California Water Plan. For situations where water suppliers may serve areas in more than one hydrologic region, the majority of each water supplier's Service Area Population must be in the hydrologic region being identified as a regional alliance.
- Water suppliers join through appropriate geographic scales for which these methodologies can be applied. For this provision, water suppliers' service area boundaries must be contiguous.

## Tiered Regional Alliances

In general, urban retail water suppliers can belong to only one regional alliance for the purpose of establishing and complying with urban water use targets. An exception is when regional alliances are tiered so that the members of the smallest alliance are all members of the larger alliance or alliances.

**Tiered Regional Alliances**

Regional Alliances 1, 2, 3, ...

Urban Retail Water Suppliers A, B, C, ...




FIGURE 6:  
EXAMPLE OF TIERED ALLIANCES

Figure 6 illustrates tiered alliances. For example, supplier A forms an alliance with suppliers B and C (Alliance 1). Supplier A cannot also form an alliance with suppliers J and K unless the A,J,K alliance were to include B and C as well. Water suppliers D, E, and F could comply as regional Alliance 2, or include supplier G and comply as regional Alliance 3. Alternatively, all suppliers in Figure 6. could comply as Alliance 5. The tiered alliance requirements are only for compliance with urban water use targets and do not apply to other regional water management activities or partnerships.

## Calculation of Targets and Compliance GPCD

### Calculation of Regional Targets

Water suppliers wishing to test compliance regionally are permitted to do so. Water suppliers in a regional alliance have three options for calculating their regional targets. Under the first option, which preserves maximum flexibility at the supplier level, each supplier in a regional alliance would first calculate its individual target as if it were complying individually. These individual targets should then be weighted by each supplier's population and averaged over all members in the alliance to obtain the regional target.<sup>24</sup> For the 2011 urban water management plans, suppliers may use their current population data for generating the regional targets. However, for testing compliance in 2015 and 2020, the population weighting of the individual targets must be based upon the compliance-year population data. A retail water supplier may update its target in 2015 (see Water Code section 10608.20(g) and any such modifications made to individual targets after 2011 must be incorporated into updated regional targets and reported in the compliance year 2015. For those urban retailers or alliances that choose method 2 for developing a target (see Water Code section 10608.20(b)(2)), the target must be revised and reported in 2020. A modification in any individual target or a change in membership in a regional alliance will require a recalculation of the regional target.

A second approach for an alliance to calculate a regional target is to sum up the individual supplier's gross water use and service area populations to develop regional gross water use and population. The alliance would then calculate regional base daily per capita use and choose one target method to calculate a regional target. Alliances must have all their members use the same baseline period.

A third approach is to calculate regional gross water use or population directly for the entire regional alliance area. Regional base daily per capita use and a regional water use target would be then be derived. Like the second approach, members of alliances using this approach must use the same baseline period and the same target method. A regional alliance must meet the requirements of Section 10608.22. The regional target may not exceed 95 percent of the region's 5-year Base Daily Per Capita Water Use. Methodology 3: Base Daily Per Capita Water Use describes in detail the interpretation and calculations required under Section 10608.22.

### Calculation of Regional Compliance Daily Per Capita Water Use

Gross Water Use and Service Area Population must be reported for each supplier during the compliance year. If applicable, adjustments for evapotranspiration and rainfall, fire suppression, and changes in distribution area should be made for each individual water supplier. Adjustments to Gross Water Use for extraordinary economic growth can be

<sup>24</sup> Assume there are (N) suppliers in an alliance, with individual targets  $T_i$  and population  $P_i$ , where the subscript on the individual targets and population denote the identity of each supplier. Then, total population in a regional alliance (RP) becomes:

The regional target (RT) can be derived as a weighted average of the individual supplier targets as follows:

applied either to the individual supplier's data or to the aggregate regional alliance data (but not both), depending upon availability of suitable data and methods. Regional compliance daily per capita water use shall be calculated as the aggregate regional Gross Water Use divided by the aggregate Service Area Population.

## Data Reporting for a Regional Alliance

A regional alliance must send DWR a letter stating that an alliance has been formed and provide a list of the water supplier members. This letter should be sent by July 1, 2011, for alliances formed before submitting 2010 urban water management plans, or in ninety days after an alliance has been formed after July 1, 2011. In the case of tiered alliances, a retail water supplier cannot be cited as a member of a regional alliance unless it acknowledges its membership in that alliance in its urban water management plan.

DWR will collect data pertaining to regional alliances through three documents: (1) through the individual supplier urban water management plans; (2) through the regional urban water management plans; and (3) through the regional alliance reports.

### Individual Supplier Urban Water Management Plans

All members of a regional alliance must include the following data in their individual urban water management plans unless they are participating in a regional urban water management plan (applicable urban water management plan dates are shown in parentheses):

- A list of all of its regional alliances. If a supplier is a member of tiered alliances, it must name all the alliances it is a member of
- Baseline Gross Water Use and Service Area Population (2010, 2015, 2020)
- Individual 2020 Urban Water Use Target (2010, 2015, 2020) and Interim 2015 Urban Water Use Target (2010)
- Compliance Year Gross Water Use (2015 and 2020) and Service Area Population (2010, 2015, 2020)
- Adjustments to Gross Water Use in the compliance year (2015, 2020)
- Water suppliers who choose Target Method 2 also must provide Landscaped Area Water Use and Baseline CII Water Use data (2010, 2015, 2020)
- Water Suppliers who choose Target Method 4 must provide the components of calculation as required by Target Method 4. Appendix C describes Target Method 4 and the regional compliance reporting that applies to that method (2010, 2015, 2020)

### Regional Urban Water Management Plans

Members of regional alliance can forgo submitting individual urban water management plans and submit a regional urban water management plan. These regional urban water management plans are different from the regional alliance reports in that they must meet all the urban water management plan reporting requirements. The water use target data can be reported in the regional plan in either of two ways:

- The regional plan can report all the data elements that are now required to be included in the individual urban water management plans pertaining to this program (see section above titled Individual Supplier Urban Water Management Plans), for each supplier in the alliance. It would also report the same data elements aggregated over all members in the alliance.
- The regional plan may report some data elements only in aggregate for the alliance as a whole (not for each individual member). For example, the plan may report Service Area Population only for the regional alliance if the regional population data are more accurate or available. If the Service Area Population is only reported on a regional basis, then Base Daily per Capita Use, Compliance Daily per Capita Use, and Urban Water Use Targets would be calculated and reported only on a regional basis. Water suppliers that are part of a regional alliance that only reports a regional population can only develop a regional Urban Water Use Target and comply with this target regionally. Developing individual targets and testing compliance at the individual level is not possible unless an individual Service Area Population is calculated.

## Regional Alliance Report

For regional alliances that do not submit a regional urban water management plan, DWR will require a regional alliance report. This report shall include all the water use target data elements that are now required to be included in the individual urban water management plans (see section above titled Individual Supplier Urban Water Management Plans) for each supplier in the alliance, and also shall include the alliance-level aggregates.

## Memoranda of Understanding or Agreements for Regional Alliances

DWR will not review or approve the terms of memoranda of understanding (MOUs) or legal agreements that water suppliers use to create and manage regional alliances. However, terms of the agreements shall be consistent with all applicable sections of the Water Code. DWR will presume that water suppliers understand the consequences if partner suppliers withdraw from a regional alliance.

## Compliance Assessment for Water Suppliers Belonging to a Regional Alliance

Compliance will be assessed based upon how an individual retail water supplier performs relative to its individual target or how the retail water supplier's regional alliance performs as a whole relative to its regional target. Regional alliances or wholesale suppliers are not themselves subject to compliance assessment. The following guidelines will be used to assess compliance:

- If a regional alliance meets its regional target, all suppliers in the alliance will be deemed compliant. For tiered alliances, if a smaller alliance does not meet its water use target, the member agencies can still be in compliance if a larger alliance is in compliance. Conversely, members of a smaller alliance can be in compliance if the smaller alliance complies while the larger agency fails. If a regional alliance fails to meet its regional

target, water suppliers in the alliance that meet their individual targets will be deemed compliant.

- Water suppliers in alliances that meet neither their individual targets nor their regional targets will be deemed noncompliant. These suppliers can still apply for grant funds if their application is accompanied by a plan that demonstrates how the funds being sought will bring them into compliance with their targets (Section 10608.56).

### **Withdrawal from a Regional Alliance before 2020**

If a water supplier withdraws from a regional alliance, the withdrawing water supplier must then comply individually. The water suppliers remaining in the regional alliance must revise regional baseline and target data and alliance membership in the subsequent UWMP plan. The memorandum of understanding or other legal agreements governing the alliance may define additional consequences or remedies.

### **Dissolution of a Regional Alliance before 2020**

If a regional alliance dissolves before 2020, each affected water supplier must then comply individually or form or join another alliance. An affected water supplier that had not previously submitted an individual urban water management plan (for example, if it had participated in a regional urban water management plan for a regional alliance that has dissolved) has to submit an urban water management plan or a regional water management plan. The memorandum of understanding or other legal agreements governing the alliance may define additional consequences or remedies.



## APPENDIX A

# Alternative Methodology for Service Area Population

---

Water suppliers without access to detailed population data should develop population estimates by anchoring their year 2000 residential connections to the year 2000 census population estimate, and then scaling this estimate backward and forward using data for active residential connections. The procedure for calculating population from connections first requires a water supplier to identify the census blocks that lie in its (year 2000) distribution area. The availability of a GIS distribution area map for the year 2000 makes this first step relatively easy.

If no GIS boundary map of the distribution area is available, a water supplier will have to perform this exercise manually. The U. S. Census Bureau's county/tract/block maps should serve as the primary tool for this matching exercise.<sup>25</sup> First select the appropriate county. Next, the first file labeled "CBC06xxx\_000.pdf" provides the detailed map numbering scheme for the entire county. The relevant maps from this list can then be used online or printed to locate the appropriate census blocks.

It is also relatively easy to scan a paper map of the distribution area (in 2000), digitize and geo-reference the boundary (and internal areas that need to be excluded), and overlay it electronically on a census map to identify which census blocks lie in the 2000 distribution area. Category 3 water suppliers may be able to access these capabilities through their local association of governments.

### Step 1: Finalize Census Blocks in the 2000 Distribution Area

Some census blocks may straddle the water supplier's year 2000 distribution area boundary line. In such cases, if half or more of the block's area appears to lie within the boundary, the water supplier should include it; otherwise, it should exclude the block.

Census blocks are grouped into block groups. Blocks that identify places such as college campuses, military installations, or correctional institutions are organized into a

#### What Is a Census Block?

A census block is the smallest geographical unit used by the Census Bureau. Census blocks are areas bounded on all sides by visible features, such as streets, roads, streams, and railroad tracks, and by invisible boundaries, such as city, town, township, and county limits, property lines, and short, imaginary extensions of streets and roads. Generally, census blocks are small in area; for example, a block may be bounded by city streets. However, census blocks in sparsely settled areas may contain many square miles of territory.

---

<sup>25</sup> These maps can be accessed at [http://ftp2.census.gov/geo/maps/blk2000/st06\\_California/County/](http://ftp2.census.gov/geo/maps/blk2000/st06_California/County/).

single block group that, taken together, corresponds exactly with the boundary of such a place. Census blocks associated with such institutions in the distribution area, but with wholly private sources of supply, can thus be cleanly removed from the population estimate.

Census block groups aggregate up to the next level of geography that is called a census tract. Blocks have a unique identification number only in a tract, not across tracts. When identifying blocks that lie in the distribution area, both block and tract identification numbers are needed to correctly link the selected blocks with their corresponding population data.

### What Is a Census Block Group?

A block group (BG) is a cluster of census blocks having the same first digit of their four-digit identifying numbers in a census tract. For example, block group 3 (BG 3) in a census tract includes all blocks numbered from 3000 to 3999. BGs generally contain between 600 and 3,000 people, with an average size of 1,500 people. BGs on American Indian reservations, off reservation trust lands, and special places must contain a minimum of 300 people. (Special places include correctional institutions, military installations, college campuses, worker's dormitories, hospitals, nursing homes, and group homes.)

## Step 2: Scale Population Information from Census Blocks to Distribution Area

Once the census blocks lying in the year 2000 distribution area are identified, each block's population in 2000 can be obtained from the Census Bureau's website. This requires the following steps:<sup>26</sup>

1. Go to [www.census.gov](http://www.census.gov)
2. Click on "American FactFinder" tab in left navigation column.
3. Click on "Download Center" in the left navigation column.
4. In the table that appears, click on the "Census 2000 Summary File 1 (SF-1) 100-Percent Data" link.
5. Under geographic summary level, select "All Blocks in a County (101)."
6. Follow the prompts to select state and county.
7. Under Select a Download Method, choose "Selected Detailed Tables."
8. Click on "Go."

### Place of Residence

Each person included in the census is counted at his or her usual place of residence, which is the place where he or she lives and sleeps most of the time. If a person has no usual residence, the person is counted where he or she was staying on Census Day (April 1). People temporarily away from their usual residence, such as on a vacation or business trip, are counted at their usual place of residence. People who moved around Census Day are counted at the place they consider to be their usual residence. A person's usual place of residence is not necessarily the same as legal residence or voting residence. A detailed set of enumeration rules guides how the Census Bureau counts individuals. An attempt is made to count all individuals, whether they reside in housing units or in group quarters.

<sup>26</sup> Note that these steps apply as of June 2010. Link names and other elements of the Census Bureau's website may change in future. The same caution applies to other website directions in this appendix.

9. When prompted with table choices, select at a minimum “P1. Total Population” and “P37. Group Quarters Population by Group Quarter Type.” You can select multiple tables at once by holding down the Ctrl key as you select them.
10. Click “Add” to add them to the Current Table Selections box.
11. Select “Next.”
12. Select “Start Download.”

A file will be created for the user in a delimited text format (the character “|” will be the delimiter which the user will need to specify while importing the text file into Excel for further manipulation) containing total population and any additional information the user selects by block. From this list, select the blocks identified as falling in the water supplier’s year 2000 actual distribution area in Step 1 and obtain the aggregate population for the water supplier’s service area.

In most cases, additional editing or manipulation of total year 2000 population should not be required. Census blocks associated with privately supplied customers would already have been removed from the distribution area definition. However, if additional privately supplied customers need to be removed from the population count, the group quarter population estimates may be used to identify the population associated with such customers and the relevant block level group quarter population estimates subtracted from total population.

### **P1. Total Population**

The “Total Population” selection includes population residing in housing units as well as in group quarters. Housing units include structures such as single-family homes, multifamily homes, mobile homes, boats, RVs, and vans. Group quarters include institutions such as correctional facilities, nursing homes, hospital wards and hospices, psychiatric hospitals, juvenile institutions, college dormitories, military quarters, agriculture worker’s dormitories, logging camps, and other institutions. The full list of what is included in group quarters is long and is intended to capture a variety of residency scenarios to make the population count as complete as possible. This list can be obtained from the Census Bureau’s website.

### **P37. Group Quarters Population by Group Quarter Type**

This selection provides a breakdown of the group quarter population into the following categories: correctional institutions; nursing homes; other institutionalized populations; college dormitories including college quarters off campus; military quarters; other non-institutional group quarters.

## **Step 3: Obtain Population by Structure Type**

To estimate population per connection, agencies are advised to develop at least two separate ratios: one for population per single-family connection, and one for population per multifamily connection, which includes apartment complexes and other types of group quarters. This information can also be obtained from the Census Bureau website.

1. Go to [www.census.gov](http://www.census.gov)
2. Click on “American FactFinder” tab in left navigation column.
3. Click on “Download Center” in the left navigation column.
4. Select the “Census 2000 Summary File 3 (SF-3) Sample Data” link.
5. Under geographic summary level, select “All Block Groups in a County (150).”
6. Follow the prompts to select state and county.

7. Under Select Download Method, select "Select Detailed Tables."
8. Click on "Go."
9. When prompted with table choices, select at a minimum "P1. Total Population" and "H33. Total Population in Occupied Housing Units by Tenure by Units in Structure."
10. Click on "Next."
11. Click on "Start Download."

A file will be created for the user in a delimited text format (the character "|" will be the delimiter which the user will need to specify while importing the text file into Excel for further manipulation) containing total population split across many categories. Also, these data are for block groups, not blocks. The first letter in a block's identifier indicates the block group it belongs to. Total population in a block group obtained from Summary File 3 may not exactly match block group population were it to be estimated from Summary File 1 for the purpose of comparison. This is because the former is created from a sample, the latter from the full data. Sample weights ensure that the two estimates of total population converge for higher levels of aggregation, such as a county, but they may not exactly match at the block-group level.

Group quarters are not included in the definition of housing units. Therefore, total population residing in occupied housing units does not include residents of group quarters. Therefore, total population must also be obtained from Summary File 3.

### H33. Total Population in Occupied Housing Units by Tenure by Units in Structure

This selection provides a breakdown of population by the following types of structures:

Owner occupied, 1 detached unit in structure  
 Owner occupied, 1 attached unit in structure  
 Owner occupied, 2 units in structure  
 Owner occupied, 3-4 units in structure  
 Owner occupied, 5-9 units in structure  
 Owner occupied, 10-19 units in structure  
 Owner occupied, 20-49 units in structure  
 Owner occupied, 50 or more units in structure  
 Owner occupied, mobile home  
 Owner occupied, boat, RV, van, etc.  
 (Repeated for renters)

## Step 4: Obtain Active Connections Data

Water suppliers differ in their metering of certain structure types. For example, some water suppliers may typically use individual metering of single-family attached structures, while other water suppliers may use master-metering. Water suppliers must first decide, based upon local knowledge and level of detail available in the billing system, how different structure types will be allocated to either the single-family or multifamily category.

For each baseline year (and the census year 2000 if it is not included in the baseline period), tabulate total single-family and total multifamily connections. Remove from the tabulation any connections that were inactive during the entire year.

For each block group, aggregate population for the single-family structure category, including both renters and owners. Subtract this estimate from total block group population obtained from Summary File 3. The difference is an estimate of population residing in multifamily structures, including group quarters.

Develop a ratio for each block group indicating how its total population is split between the single-family and multifamily structures. Then, for each block in the distribution area, apply its corresponding block-group ratio to split the block-level total population (from Summary File 1) into the single-family and multifamily categories. Aggregate these block-specific splits to obtain total population residing in single-family and multifamily structures in the entire distribution area.

## Step 5: Develop Population Estimates for Non-Census Years

For the census year 2000, obtain persons per single-family connection and per multifamily connection. Apply these ratios to active connections data for the non-census years to estimate non-census-year population. Figure A-1 provides a pictorial description of the approach outlined above.




FIGURE A-1  
POPULATION PER RESIDENTIAL CONNECTION METHOD

Two exceptions to this procedure are possible:

- Water suppliers are permitted to split their multifamily accounts into additional categories. For example, water suppliers may divide the multifamily sector into categories based upon units in the structure, assuming such information is reliably recorded in their billing system. The water supplier can calculate persons-per-connection for each of these categories, as long as they use the same methodology for all base period and compliance years. Water suppliers may substitute a person-per-unit

ratio in place of a person-per-connection ratio to scale multifamily population if their billing systems include reliable data about total units in each multifamily structure. In such a case, population in group quarters would need to be scaled separately using a persons-per-connection ratio specific to group quarters.

- Water suppliers that cannot identify multifamily connections at present should use a single ratio (total population per single-family connection) to obtain population for the non-census years. DWR recommends that these water suppliers begin improving their data systems so that population estimates for the 2015 and 2020 compliance years are more accurate. DWR also encourages water suppliers to identify multifamily accounts separately from CII accounts.

## Step 6: Further Improvements to Estimates

Water suppliers that calculate population using the per-connection method described here are encouraged to improve these estimates by including auxiliary information from other sources such as the California Department of Finance, Current Population Survey, the American Housing Survey, building permits data, and similar sources. If they use such information they should maintain consistency between the baseline and compliance years, document the methodology, and provide details about the magnitude of the adjustments made to the population estimated using Steps 1 through 5.

## APPENDIX B

# Model Water Efficient Landscape Ordinance Definitions and Calculations

---

The Model Water Efficient Landscape Ordinance (MWELO) was originally added to the California Code of Regulations (Title 23, Division 2, Chapter 2.7) in 1992 and was revised in 2009. Paragraph 492.4 defines the calculation of Maximum Applied Water Allowance (MAWA).

For landscaped areas that are installed on or after January 1, 2010, the MAWA equation and all applicable definitions of terms from the revised ordinance are as follows:

*Maximum Applied Water Allowance (MAWA) = (ET<sub>o</sub>) (0.62) [(0.7 x LA) + (0.3 x SLA)]*

*Maximum Applied Water Allowance (MAWA) is in gallons per year*

*ET<sub>o</sub> = Reference Evapotranspiration (inches per year). Reference evapotranspiration is used as the basis of determining the Maximum Applied Water Allowance so that regional differences in climate can be accommodated." Reference Evapotranspiration values for each location can be found in Appendix A of the 2010 Model Water Efficient Landscape Ordinance.*

*0.62 = Conversion Factor (from inches/year to gallons/sq ft/year)*

*0.7 = ET Adjustment Factor (ETAF). When applied to reference evapotranspiration, the ETAF "adjusts for plant factors and irrigation efficiency, two major influences upon the amount of water that needs to be applied to the landscape."*

*LA = Landscaped Area including SLA (square feet), which includes "all the planting areas, turf areas, and water features in a landscape design plan subject to the Maximum Applied Water Allowance calculation. The landscape area does not include footprints of buildings or structures, sidewalks, driveways, parking lots, decks, patios, gravel or stone walks, other pervious or non-pervious hardscapes, and other non-irrigated areas designated for non-development (e.g., open spaces and existing native vegetation)."*

*0.3 = Additional Water Allowance for Special Landscape Area (SLA), resulting in an effective ETAF for SLA of 1.0.*

*SLA = Special Landscaped Area (square feet), which is defined as "an area of the landscape dedicated solely to edible plants, areas irrigated with recycled water, water features using recycled water and areas dedicated to active play such as parks, sports fields, golf courses, and where turf provides a playing surface."*

For landscaped areas that are installed before January 1, 2010, the MAWA equation and all applicable definition of terms from the original 1992 version of the ordinance are as follows:

$$\text{Maximum Applied Water Allowance (MAWA)} = (ET_o) (0.62) (0.8 \times LA)$$

*Maximum Applied Water Allowance (MAWA) is in gallons per year*

*ET<sub>o</sub> = Reference Evapotranspiration (inches per year). Reference Evapotranspiration values for each location can be found on page 38.10 of the Model Water Efficient Landscape Ordinance.*

*0.62 = Conversion Factor (from inches/year to gallons/sq ft/year)*

*0.8 = ET Adjustment Factor (ETAF). When applied to reference evapotranspiration, the ETAF “adjusts for plant factors and irrigation efficiency, two major influences upon the amount of water that needs to be applied to the landscape.”*

*LA = Landscaped area includes the entire parcel less the building footprint, driveways, non-irrigated portions of parking lots, landscapes such as decks and patio, and other non-porous areas. Water features are included in the calculation of the landscaped area. Areas dedicated to edible plants, such as orchards or vegetable gardens are not included.*



## Appendix C

### Method 4 for Determining Water Use Targets

---

*TO BE DEVELOPED*

## Appendix D

# Regulations for Implementing Process Water Provisions

---

*TO BE DEVELOPED*